



Main

Circuit breaker application	Distribution
Range	Acti 9
Product name	IC60 RCBO
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Device short name	IC60H2 RCBO
Poles description	2P
[In] rated current	20 A at 50 °C
Earthing system	IT TN TT
Curve code	C
Earth-leakage sensitivity	30 mA
Breaking capacity	Icn : 10000 A - 110 V - AC at 50/60 Hz

Complementary

Neutral position	Left
Number of protected poles	1
Device location in system	Outgoer
Network type	AC
Network frequency	50 Hz
[Ue] rated operational voltage	Ue: 110 V - AC at 50/60 Hz
Trip unit technology	Thermal-magnetic
Residual current tripping technology	Voltage dependent
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Class A
[Icw] rated short-time withstand current	Icw: 250 A during 8/20 µs impulse withstand
[Ics] rated service breaking capacity	Ics: 7500 A - 110 V - AC at 50/60 Hz
Limitation class	3
[Ui] rated insulation voltage	Ui: 400 V - AC at 50/60 Hz
[Uimp] rated impulse withstand voltage	Uimp: 4 kV
Suitability for isolation	Yes
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar distribution block compatibility	NO
9 mm pitches	4
Height	11 mm
Width	36 mm
Depth	75.5 mm
Product weight	332 g
Colour	White
Mechanical durability	20000 cycles
Electrical durability	5000 cycles

Provision for padlocking	Padlockable with padlock Ø 4 mm
Locking options description	ON/OFF locking facilities
Connections - terminals	Screw clamp terminal connection on top - 1...25 mm ² - rigid - without cable end Screw clamp terminal connection on top - 1...16 mm ² - flexible Screw clamp terminal connection on bottom - 1...16 mm ² - rigid - without cable end Screw clamp terminal connection on bottom - 1...10 mm ² - flexible
Wire stripping length	13 mm on bottom of power circuit 14 mm on top of power circuit
Tightening torque	3.5 N.m on top of power circuit 2 N.m on bottom of power circuit
Earth-leakage protection	Integrated

Environment

standards	IEC 61009-1 IEC 61009-2-2 AS/NZS 61009.1
IP degree of protection	IP20
tropicalisation	2
relative humidity	95 % at 55 °C
ambient air temperature for operation	-15...60 °C
ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1245 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available