

## A9D32610

earth leakage circuit breaker iDPN N Vigi - 1P + N - 10A - 30mA class A



### Main

Device application	Distribution
Range	Acti 9
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Product name	IDPN Vigi
Device short name	IDPN N Vigi
Poles description	1P + N
Neutral position	Left
Number of protected poles	1
[In] rated current	10 A
Network type	AC
Curve code	C
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Class A
Breaking capacity	Icn 6000 A at 230 V AC 50 Hz conforming to EN/IEC 61009-1 Icn 6000 A at 230 V AC 50 Hz conforming to EN/IEC 61009-2-1
Suitability for isolation	Yes conforming to IEC 60947-1

### Complementary

Device location in system	Outgoer
Network frequency	50 Hz
[Ue] rated operational voltage	230 V AC 50 Hz
Trip unit technology	Thermal-magnetic
Magnetic tripping limit	5...10 x In
Residual current tripping technology	Voltage independent
[Ics] rated service breaking capacity	6000 A at 230 V AC 50 Hz conforming to EN/IEC 61009-1 6000 A at 230 V AC 50 Hz conforming to EN/IEC 61009-2-1
Limitation class	3 conforming to EN/IEC 61009-1 3 conforming to EN/IEC 61009-2-1
[Ui] rated insulation voltage	400 V AC 50 Hz
[Uimp] rated impulse withstand voltage	4 kV
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON, OFF, fault trip
Mounting support	DIN rail
Comb busbar distribution block compatibility	YES top or bottom :
Connection pitch	
9 mm pitches	4
Height	85 mm
Width	36 mm
Depth	73 mm
Product weight	125 g
Colour	White

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Mechanical durability	20000 cycles
Electrical durability	20000 cycles
Locking options description	Sealable Padlock in on or off position
Connections - terminals	Single terminal 1...16 mm <sup>2</sup> rigid Single terminal 1...10 mm <sup>2</sup> flexible with cable end Single terminal 1...10 mm <sup>2</sup> flexible without cable end
Wire stripping length	15 mm
Tightening torque	3.5 N.m
Earth-leakage protection	Integrated

## Environment

standards	EN/IEC 61009-1 EN/IEC 61009-2-1
product certifications	VDE VDE RCM KEMA
IP degree of protection	IP20 conforming to IEC 60529
pollution degree	3
overvoltage category	III conforming to IEC 60364
electromagnetic compatibility	8/20 µs impulse withstand, 250 A conforming to EN/IEC 61009-1 8/20 µs impulse withstand, 250 A conforming to EN/IEC 61009-2-1
tropicalisation	2 conforming to IEC 60068-1
relative humidity	95 % ( 55 °C )
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...85 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1214 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations