

A9E16067

iRTC relay- delays de-energizing a load upon opening- 1 O/C - Uc 24-240VAC/24VDC



Main

Relay application	Time delay relay
Time delay type	Delays de-energizing of a load upon contact opening
Range	Acti 9
Product name	IRT
Device short name	IRTCT
Signal contacts composition	1 C/O

Complementary

[Ie] rated operational current	8 A AC 250 V 8 A DC 250 V 0.01 A DC 5 V
Impulse duration	> 100 ms
Local signalling	LED flashing time delay
Type of setting	Time delay configuration by rotary knob
Time delay range	0.1...360000 s
Accuracy error	+/- 10 %
Repeat accuracy	+/- 0.5 %
Control circuit voltage	24 V DC 24...240 V AC 50/60 Hz 24...240 V AC 50/60 Hz
[Us] rated supply voltage	24 V DC 24...240 V AC 50/60 Hz 24...240 V AC 50/60 Hz
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	93 mm
Width	18 mm
Depth	72 mm
Product weight	0.065 kg
Colour	White
Mechanical durability	>= 5000000 cycles
Electrical durability	AC-1 : >= 100000 cycles
Undervoltage behaviour	100 ms
Connections - terminals	Tunnel type terminals 2 cable(s) 1.5 mm ² flexible with cable end Tunnel type terminals 2 cable(s) 1.5 mm ² flexible without cable end Tunnel type terminals 2 cable(s) 2.5 mm ² rigid with cable end Tunnel type terminals 2 cable(s) 2.5 mm ² rigid without cable end

Environment

IP degree of protection	IP20
immunity to microbreaks	<= 20 ms
ambient air temperature for operation	-5...55 °C
ambient air temperature for storage	-40...70 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1243 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available