



### Main

Range of product	IPB
Range	Acti 9
Product name	Acti 9 iPB
Product or component type	Push-button
Device short name	IPB
Standards	IEC 60669-1 IEC 60947-5-1

### Complementary

Contacts type and composition	1 NO
[Ie] rated operational current	20 A
[Ue] rated operational voltage	250 V AC
Control type	1 push-button grey
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Comb busbar distribution block compatibility	Upside : Libro Upside : ProDis Upside : Clario
9 mm pitches	2
Height	82 mm
Width	18 mm
Depth	71 mm
Colour	White
Electrical durability	AC-22 : 30000 cycles AC 50/60 Hz
Connections - terminals	Staggered tunnel terminal 2 cable(s) 0.5...2.5 mm <sup>2</sup> flexible with cable end Staggered tunnel terminal 2 cable(s) 0.5...2.5 mm <sup>2</sup> flexible without cable end Staggered tunnel terminal 2 cable(s) 0.5...2.5 mm <sup>2</sup> rigid with cable end Staggered tunnel terminal 2 cable(s) 0.5...2.5 mm <sup>2</sup> rigid without cable end
Wire stripping length	9 mm
Tightening torque	1 N.m

### Environment

tropicalisation	2
relative humidity	95 % ( 55 °C )
ambient air temperature for operation	-35...70 °C
ambient air temperature for storage	-40...80 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations