



Main

| | |
|---------------------------|------------------------------|
| Range of product | IPB |
| Range | Acti 9 |
| Product name | Acti 9 iPB |
| Product or component type | Push-button |
| Device short name | IPB |
| Standards | IEC 60669-1 IEC 60947-5-1 |

Complementary

| | |
|--|--|
| Contacts type and composition | 1 NC 1 NO |
| [Ie] rated operational current | 20 A |
| [Ue] rated operational voltage | 250 V AC |
| Control type | 2 push-button green/red |
| Mounting mode | Fixed |
| Mounting support | 35 mm symmetrical DIN rail |
| Comb busbar distribution block compatibility | Upside : Libro Upside : ProDis Upside : Clario |
| 9 mm pitches | 2 |
| Height | 82 mm |
| Width | 18 mm |
| Depth | 71.5 mm |
| Colour | White |
| Electrical durability | AC-22 : 30000 cycles AC 50/60 Hz |
| Connections - terminals | Staggered tunnel terminal 2 cable(s) 2.5 mm ² flexible with cable end Staggered tunnel terminal 2 cable(s) 2.5 mm ² flexible without cable end Staggered tunnel terminal 2 cable(s) 2.5 mm ² rigid with cable end Staggered tunnel terminal 2 cable(s) 2.5 mm ² rigid without cable end |

Environment

| | |
|---------------------------------------|----------------|
| tropicalisation | 2 |
| relative humidity | 95 % (55 °C) |
| ambient air temperature for operation | -20...50 °C |
| ambient air temperature for storage | -40...80 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYYYWW) | Compliant - since 1001 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |