



Main

| | |
|-----------------------------|-------------------------|
| Range | Acti 9 |
| Product name | Acti 9 iLL |
| Product or component type | Modular pilot lighth |
| Device short name | iLL |
| Light source | LED |
| Cap/operator or lens colour | White |
| [Us] rated supply voltage | 110...230 V AC 50/60 Hz |

Complementary

| | |
|--|--|
| Bulb lifespan | 100000 h |
| Local signalling | 1 lamp |
| Power consumption | 0.3 W |
| Mounting mode | Fixed |
| Mounting support | Symmetrical DIN rail |
| Comb busbar distribution block compatibility | Upside : ProDis |
| 9 mm pitches | 2 |
| Height | 82 mm |
| Width | 18 mm |
| Depth | 69.5 mm |
| Auxiliary connection terminal | Tunnel type terminal 2 cable(s) flexible 2.5 mm ² with cable end Tunnel type terminal 2 cable(s) flexible 2.5 mm ² without cable end Tunnel type terminal 2 cable(s) rigid 2.5 mm ² with cable end Tunnel type terminal 2 cable(s) rigid 2.5 mm ² without cable end |

Environment

| | |
|---------------------------------------|----------------|
| standards | IEC 60947-5-1 |
| IP degree of protection | IP2 IPxx B |
| pollution degree | 3 |
| tropicalisation | 2 |
| relative humidity | 95 % (55 °C) |
| ambient air temperature for operation | -20...50 °C |
| ambient air temperature for storage | -40...100 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYYY) | Compliant - since 1001 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |