



### Main

Range	Acti 9
Product name	Acti 9 iLL
Product or component type	Modular pilot lighth
Device short name	iLL
Light source	LED
Cap/operator or lens colour	Yellow
[Us] rated supply voltage	110...230 V AC 50/60 Hz

### Complementary

Bulb lifespan	100000 h
Local signalling	1 lamp
Power consumption	0.3 W
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
Comb busbar distribution block compatibility	Upside : ProDis
9 mm pitches	2
Height	82 mm
Width	18 mm
Depth	69.5 mm
Auxiliary connection terminal	Tunnel type terminal 2 cable(s) flexible 2.5 mm <sup>2</sup> with cable end Tunnel type terminal 2 cable(s) flexible 2.5 mm <sup>2</sup> without cable end Tunnel type terminal 2 cable(s) rigid 2.5 mm <sup>2</sup> with cable end Tunnel type terminal 2 cable(s) rigid 2.5 mm <sup>2</sup> without cable end

### Environment

standards	IEC 60947-5-1
IP degree of protection	IP2 IPxx B
pollution degree	3
tropicalisation	2
relative humidity	95 % ( 55 °C )
ambient air temperature for operation	-20...50 °C
ambient air temperature for storage	-40...100 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations