

A9XAH657

Acti 9 - comb busbar cut - 3P - type L+Aux - 18 mm pitch - 57 modules - 100A



Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	3P
Number of ways	38 ways, type : L + auxiliary (tooth) with 18 mm pitch
Distance between way	27 mm
Marking	L1 L2 L3
Total number of 18 mm modules	57

Complementary

Insulation	Insulated
Device presentation	Cuttable
Provided equipment	End piece : set of 10
[Ie] rated operational current	100 A (40 °C)
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal
9 mm pitches	114
Width	1000 mm
Colour	White (RAL 9003)
Range compatibility	Acti 9 / Acti 9 iC60 Acti 9 / Acti 9 iK60 Acti 9 / Acti 9 iID Acti 9 / Acti 9 iID K Acti 9 / Acti 9 iSW Acti 9 / Acti 9 iSW-NA Multi 9 / Multi 9 C60 / C60H Multi 9 / Multi 9 C60 / C60N Multi 9 / Multi 9 C60 / C60L Multi 9 / Multi 9 C60 / C60CTRL

Environment

standards	IEC 61439-2 IEC 60947-7-1 IEC 60947-7-1
fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
pollution degree	3 conforming to IEC 60947-7-1

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1336 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold