

## A9XPH112

Acti 9 - comb busbar cut - 1P - type 1L - 18 mm pitch  
- 12 modules - 100A



### Main

|                                    |  |
|------------------------------------|--|
| Range                              | Acti 9                                       |
| Product or component type          | Comb busbar                                  |
| Accessory / separate part category | Connection accessory                         |
| Poles description                  | 1P   |
| Number of ways                     | 12 ways, type : 1 L (tooth) with 18 mm pitch |
| Distance between way               | 18 mm  |
| Marking                            | L  |
| Total number of 18 mm modules      | 12   |

### Complementary

|                                |  |
|--------------------------------|--|
| Insulation                     | Insulated  |
| Device presentation            | Cuttable   |
| [Ie] rated operational current | 100 A ( 40 °C )  |
| [Ue] rated operational voltage | 415 V AC   |
| [Ui] rated insulation voltage  | 500 V AC conforming to IEC 61439-2   |
| Mounting mode                  | Horizontal   |
| Mounting location              | Top or bottom on tunnel type terminals<br>Top or bottom on double terminal   |
| 9 mm pitches                   | 24   |
| Width                          | 220 mm   |
| Colour                         | White ( RAL 9003 )   |
| Range compatibility            | Acti 9 / Acti 9 iC60<br>Acti 9 / Acti 9 iK60<br>Acti 9 / Acti 9 iID<br>Acti 9 / Acti 9 iID K<br>Acti 9 / Acti 9 iSW<br>Acti 9 / Acti 9 iSW-NA<br>Multi 9 / Multi 9 C60 / C60H<br>Multi 9 / Multi 9 C60 / C60N<br>Multi 9 / Multi 9 C60 / C60L<br>Multi 9 / Multi 9 C60 / C60CTRL |

### Environment

|                  |   |
|------------------|---|
| standards        | IEC 61439-2<br>IEC 60947-7-1<br>IEC 60947-7-1 |
| fire resistance  | 960 °C ( 30 s ) conforming to IEC 60695-2-1   |
| pollution degree | 3 conforming to IEC 60947-7-1                 |

### Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product   |
| RoHS (date code: YYWW)   | Compliant - since 1336 - Schneider Electric declaration of conformity |
| REACH                    | Reference not containing SVHC above the threshold                     |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.