

A9XPH212

Acti 9 - comb busbar cut - 2P - type N+1L - 18 mm pitch - 12 modules - 100A



Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	1P + N
Number of ways	6 ways, type : N + 1 L (tooth) with 18 mm pitch
Distance between way	36 mm
Marking	N L
Total number of 18 mm modules	12

Complementary

Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	100 A (40 °C)
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal
9 mm pitches	24
Width	220 mm
Colour	White (RAL 9003)
Range compatibility	Acti 9 / Acti 9 iC60 Acti 9 / Acti 9 iK60 Acti 9 / Acti 9 iLD Acti 9 / Acti 9 iLD K Acti 9 / Acti 9 iSW Acti 9 / Acti 9 iSW-NA Multi 9 / Multi 9 C60 / C60H Multi 9 / Multi 9 C60 / C60N Multi 9 / Multi 9 C60 / C60L Multi 9 / Multi 9 C60 / C60CTRL

Environment

standards	IEC 61439-2 IEC 60947-7-1 IEC 60947-7-1
fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
pollution degree	3 conforming to IEC 60947-7-1

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1336 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.