A9XPH224

Acti 9 - comb busbar - 1L+N - 18 mm pitch - 24 modules - 100 A





Main

Range	Acti 9	
Product or component type	Comb busbar	
Accessory / separate part category	Connection accessory	
Lines description	1L + N	
Total number of 18 mm modules 24		

Complementary

Number of ways	12 ways N + 1 L
Poles configuration for 1 way	1 x 1P + N 1 x 2P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	36 mm
Marking	N L
Insulation	Insulated
Device presentation	Cuttable
[le] rated operational current	100 A (40 °C)
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal
9 mm pitches	48
Width	430 mm
Colour	White (RAL 9003)
Range compatibility	Multi 9 C60 Acti 9 iK60 Acti 9 iK60 Acti 9 iC60 Acti 9 iID Acti 9 iID K Acti 9 iSW Acti 9 iSW

Environment

standards	IEC 61439-2 IEC 60947-7-1	:
fire resistance	960 °C (30 s) conforming to IEC 60695-2-1	
pollution degree	3 conforming to IEC 60947-7-1	_
IP degree of protection	IP20 with end-pieces and tooth covers	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1336 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold

Need no specific recycling operations

