## **A9XPH324**

N/ain

Acti 9 - comb busbar cut - 3P - type 3L - 18 mm pitch - 24 modules - 100A

# Contraction of the contraction o

Main	
Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	3P
Number of ways	8 ways, type: 3 L (tooth) with 18 mm pitch
Distance between way	54 mm
Marking	L1 L2 L3
Total number of 18 mm modul	les 24

#### Complementary

Insulation	Insulated
Device presentation	Cuttable
[le] rated operational current	100 A ( 40 °C )
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal
9 mm pitches	48
Width	430 mm
Colour	White ( RAL 9003 )
Range compatibility	Acti 9 / Acti 9 iC60 Acti 9 / Acti 9 iK60 Acti 9 / Acti 9 iID Acti 9 / Acti 9 iID K Acti 9 / Acti 9 iSW Acti 9 / Acti 9 iSW Acti 9 / Acti 9 iSW-NA Multi 9 / Multi 9 C60 / C60H Multi 9 / Multi 9 C60 / C60N Multi 9 / Multi 9 C60 / C60L Multi 9 / Multi 9 C60 / C60CTRL

### **Environment**

standards	IEC 61439-2	_
	IEC 60947-7-1	
	IEC 60947-7-1	
fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1	
pollution degree	3 conforming to IEC 60947-7-1	_

#### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1336 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold