

## CR1F265U7

TeSys F magnetic latching contactor - 3P(3 NO) -  
265 A - 240 V AC coil



### Main

Range	TeSys
Product name	TeSys F
Product or component type	Magnetic latching contactor
Device short name	CR1F
Device application	Control
Contactor application	Motor control Resistive load
Utilisation category	AC-1 AC-3 AC-4
Poles description	3P
Pole contact composition	3 NO
[Ue] rated operational voltage	1000 V AC 25...200 Hz
[Ie] rated operational current	350 A (<= 40 °C) at <= 440 V AC AC-1 265 A (<= 40 °C) at <= 440 V AC AC-3 245 A (<= 40 °C) at <= 440 V AC AC-4
Motor power kW	132 kW 400 V AC 50/60 Hz AC-4
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	240 V AC 50/60 Hz
Irms rated making capacity	2940 A
Rated breaking capacity	2450 A at 220...440 V 2200 A at 500 V 800 A at 1000 V 1700 A at 660/690 V
[Icw] rated short-time withstand current	2200 A <= 40 °C 10 s 1230 A <= 40 °C 30 s 950 A <= 40 °C 1 min 620 A <= 40 °C 3 min 480 A <= 40 °C 10 min 2200 A <= 40 °C 1 s 2200 A <= 40 °C 5 s
Associated fuse rating	315 A aM at <= 440 V 400 A gG at <= 440 V 400 A BS88 at <= 440 V
Average impedance	0.32 mOhm at 50 Hz - Ith 350 A
[Ui] rated insulation voltage	1500 V conforming to VDE 0110 group C 1000 V conforming to IEC 60158-1 1000 V conforming to IEC 60947-4 1000 V conforming to BS 775
Power dissipation per pole	22 W AC-3 39 W AC-1
Connections - terminals	Lugs-ring terminals 1 cable(s) 240 mm <sup>2</sup> Connector 1 cable(s) 240 mm <sup>2</sup> Bars 2 x (32 x 4 mm) Power circuit : bolted connection
Tightening torque	35 N.m
Operating time	50...100 ms unlatching 40...75 ms latching
Mechanical durability	1 Mcycles
Operating rate	120 cyc/h at <= 40 °C

### Complementary

Control circuit voltage limits	0.85...1.1 Uc latching
--------------------------------	------------------------

0.85...1.1 Uc unlatching

Average coil consumption	1650 VA AC 50/60 Hz latching 9 VA AC 50/60 Hz unlatching
--------------------------	---

## Environment

protective treatment	TC
ambient air temperature for operation	-15...70 °C
ambient air temperature for storage	-60...80 °C
operating altitude	3000 m without derating in temperature
height	203 mm
width	201.5 mm
depth	213 mm
product weight	7.4 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1028 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available