# KAA1H

operating head for cam switch -  $\emptyset$  29 mm - black handle



#### Main

| Range of product          | Harmony Series K                                  |
|---------------------------|---|
| Product or component type | Cam switch operating head                         |
| Component name            | KAA   |
| Product compatibility     | Front mounting bodies 12 and 20 A by Ø 22 mm hole |
| Cam switch head type      | With bezel Ø 29 mm, plastic with metallic finish  |
| Type of operator          | Black handle, length = 35 mm                      |
| Rotary handle padlocking  | Without   |
| Presentation of legend    | With mat black legend                             |

## Complementary


| Mechanical durability | 1000000 cycles |  |
|-----------------------|----------------|--|
| CAD overall width     | 29 mm          |  |
| CAD overall height    | 38 mm          |  |
| CAD overall depth     | 77 mm          |  |
| Length                | 35 mm          |  |
| Product weight        | 0.042 kg       |  |

#### **Environment**

|                                       |  | -   |
|---------------------------------------|--|-----|
| protective treatment                  | TC   |     |
| ambient air temperature for operation | -2555 °C   | - 0 |
| ambient air temperature for storage   | -4070 °C   | - 1 |
| shock resistance                      | 30 gn conforming to IEC 68-2-27                              |     |
| vibration resistance                  | 5 gn, 10150 Hz conforming to IEC 68-2-6                      |     |
| IP degree of protection               | IP65 conforming to IEC 529<br>IP65 conforming to NF C 20-010 |     |

### **Operating Head**

For Ø 22 mm/0.87 in. Hole, Front Mounting Body



#### **Operating Head**

Panel Cut-out

