

# LTMR08MFM

motor controller LTMR TeSys T - 100..240 V AC 8 A for Modbus



## Main

|                             |  |
|-----------------------------|--|
| Range                       | TeSys  |
| Product name                | TeSys T  |
| Device short name           | LTMR   |
| Product or component type   | Motor controller   |
| Device application          | Equipment monitoring and control   |
| Measurement current         | 0.4...8 A  |
| [Us] rated supply voltage   | 100...240 V AC 50/60 Hz  |
| Current consumption         | 8...62.8 mA  |
| Supply voltage limits       | 93.5...264 V AC  |
| Communication port protocol | Modbus   |
| Bus type                    | Modbus 2-wire RS 485 interface, addressing 1...247, transmission rate 1.2...19.2 kbit/s, RJ45 with 2 shielded twisted pairs<br>Modbus 2-wire RS 485 interface, addressing 1...247, transmission rate 1.2...19.2 kbit/s, terminal block with 2 shielded twisted pairs |

## Complementary

|  |  |
|--|--|
| [Ui] rated insulation voltage          | 690 V conforming to UL 508<br>690 V conforming to CSA C22.2 No 14<br>690 V conforming to EN/IEC 60947-1  |
| [Uimp] rated impulse withstand voltage | 4 kV for supply, inputs and outputs conforming to EN/IEC 60947-4-1<br>6 kV for current or voltage measurement circuit conforming to EN/IEC 60947-4-1<br>0.8 kV for communication circuit conforming to EN/IEC 60947-4-1  |
| Short-circuit withstand                | 100 kA conforming to EN/IEC 60947-4-1  |
| Associated fuse rating                 | 0.5 A gG for control circuit<br>4 A gG for output  |
| Protection type                        | Earth-leakage protection<br>Phase failure<br>Reverse polarity protection<br>Thermal overload protection<br>Thermal protection<br>Overload<br>Phase unbalance<br>Locked rotor<br>Overload (long time)<br>Load fluctuation<br>Power factor variation   |
| Network and machine diagnosis type     | Phase fault and earth fault trip counters<br>Remaining operating time before overload tripping<br>Running hours counter/operating time<br>Starting current and time<br>Waiting time after overload tripping<br>Fault recording<br>Event recording<br>Trip context information<br>Trip history information<br>Motor control command recording |
| Logic input number                     | 6  |
| Input current                          | 3.1 mA at 100 V<br>7.5 mA at 240 V   |
| Current state 0 guaranteed             | Logic input : 0...40 V and $\leq 15$ mA for 25 ms  |
| Current state 1 guaranteed             | Logic input : 79...264 V and $\geq 2$ mA for 25 ms   |
| Maximum operating frequency            | 2 Hz   |
| Load current                           | 5 A at 250 V AC for logic output   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                               |   |
|-------------------------------|---|
|                               | 5 A at 30 V DC for logic output   |
| Permissible power             | 480 VA (AC-15), I <sub>e</sub> = 2 A, 500000 cycles (output)<br>30 W (DC-13), I <sub>e</sub> = 1.25 A, 500000 cycles (output)   |
| Operating rate                | 1800 cyc/h  |
| Contacts type and composition | 1 NO + 1 NC fault signal<br>3 NO  |
| Metering type                 | Earth-fault current<br>Phase current I <sub>1</sub> , I <sub>2</sub> , I <sub>3</sub> RMS<br>Temperature<br>Average current I <sub>avg</sub><br>Imbalance current   |
| Measurement accuracy          | +/- 30 min/year internal clock<br>0,02 temperature<br>5...15 % earth fault current internal measurement (for current > 0.1 A)<br>1 % current<br>1 % voltage (100...830 V)<br>5 % active and reactive power<br>5 % earth fault current external measurement (< 5 % or 0.01 A)<br>3 % power factor (cos φ > 0.6)  |
| Overvoltage category          | III   |
| Connection pitch              | 5.08 mm   |
| Connections - terminals       | Connector, 1 flexible cable with cable end 0.25...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit<br>Connector, 1 flexible cable without cable end 0.2...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit<br>Connector, 1 flexible cable without cable end 0.25...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit<br>Connector, 1 solid cable without cable end 0.2...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit<br>Connector, 2 flexible cable with cable end 0.2...1 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit<br>Connector, 2 flexible cable without cable end 0.2...1.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit<br>Connector, 2 flexible cable without cable end 0.5...1.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit<br>Connector, 2 solid cable without cable end 0.2...1 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit  |
| Tightening torque             | 0.5...0.6 N.m, 3 mm flat screwdriver for control circuit  |
| Pollution degree              | 3   |
| Electromagnetic compatibility | <ul style="list-style-type: none"> <li>● electrostatic discharge 3 (8 kV air, 6 kV contact), conforming to EN/IEC 61000-4-2</li> <li>● fast transients immunity test other circuits level 3 (2 kV), conforming to EN/IEC 61000-4-4</li> <li>● fast transients immunity test on supply and relay outputs level 4 (4 kV), conforming to EN/IEC 61000-4-4</li> <li>● conducted RF disturbances (10 V), conforming to EN/IEC 61000-4-6</li> <li>● surges serial mode (1 kV) control circuit, conforming to EN/IEC 61000-4-5</li> <li>● surges common mode (2 kV) communication, conforming to EN/IEC 61000-4-5</li> <li>● surges common mode (2 kV) control circuit, conforming to EN/IEC 61000-4-5</li> <li>● radiated RF fields 3 (10 V/m), conforming to EN/IEC 61000-4-3</li> <li>● voltage dips and interruptions immunity test (70 %, 500 ms), conforming to EN/IEC 61000-4-11</li> <li>● surges serial mode (0.5 kV) temperature sensor, conforming to EN/IEC 61000-4-5</li> <li>● surges common mode (1 kV) temperature sensor, conforming to EN/IEC 61000-4-5</li> <li>● surges serial mode (2 kV) relay outputs and supply, conforming to EN/IEC 61000-4-5</li> <li>● surges common mode (4 kV) relay outputs and supply, conforming to EN/IEC 61000-4-5</li> </ul> |
| Width                         | 91 mm   |
| Height                        | 61 mm   |
| Depth                         | 122.5 mm  |
| Product weight                | 0.53 kg   |
| Web services                  | Web server  |
| Compatibility code            | LTMR  |

## Environment

|           |   |
|-----------|---|
| standards | EN 60947-4-1<br>IACS E10<br>IEC 60947-4-1<br>UL 508 |
|-----------|---|

|                                       |  |
|---------------------------------------|--|
| product certifications                | ABS<br>ATEX<br>BV<br>CCC<br>CSA<br>C-Tick<br>DNV<br>GL<br>KERI<br>LROS (Lloyds register of shipping)<br>NOM<br>RINA<br>RMRoS<br>UL<br>EAC  |
| protective treatment                  | 12 x 24 hour cycles conforming to EN/IEC 60068-2-30<br>48 h conforming to EN/IEC 60070-2-11<br>TH conforming to EN/IEC 60068   |
| fire resistance                       | 650 °C conforming to EN/IEC 60695-2-12<br>960 °C conforming to UL 94   |
| ambient air temperature for operation | -20...60 °C  |
| ambient air temperature for storage   | -40...80 °C  |
| operating altitude                    | <= 2000 m without derating   |
| mechanical robustness                 | <ul style="list-style-type: none"> <li>• shocks half sine wave acceleration (15 Gn for 11 ms) conforming to EN/IEC 60068-2-27</li> <li>• vibrations mounted on symmetrical rail (1 Gn, 5...300 Hz) conforming to EN/IEC 60068-2-6</li> <li>• vibrations plate mounted (4 Gn, 5...300 Hz) conforming to EN/IEC 60068-2-6</li> </ul> |
| IP degree of protection               | IP20   |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0501 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product environmental profile    | Available   |
| Product end of life instructions | Available   |