



Main

| | |
|---------------------------|-----------------------------|
| Range | Linery |
| Product name | BZ |
| Device short name | LA9Z |
| Product or component type | Adaptors for busbar systems |
| Number of ways | 1 way |

Complementary

| | |
|-------------------------------|---|
| Range compatibility | Prisma - G Prisma - P Compact Prisma - PH Spacial |
| Product compatibility | NSX400...630 PowerPact NL |
| Poles description | 3P |
| Permissible current | 200 A with 12 x 5 mm busbar 250 A with 15 x 5 mm busbar 320 A with 20 x 5 mm busbar 400 A with 25 x 5 mm busbar 450 A with 30 x 5 mm busbar 360 A with 12 x 10 mm busbar 520 A with 20 x 10 mm busbar 630 A with 30 x 10 mm busbar |
| [Ui] rated insulation voltage | 690 V |
| Busbar pitch | 60 mm |
| Width | 139 mm |
| Height | 270 mm |
| Depth | 63 mm |
| Colour | Anthracite grey |

Environment

| | |
|-------------------------|------------------------------|
| IP degree of protection | IP20 conforming to IEC 60529 |
|-------------------------|------------------------------|

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1121 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |