NSYS3D101030DP

Spacial S3D dbl plain door with mount.plate. H1000xW1000xD300 IP55 IK10 RAL7035.



B 4	

Range	Spacial
Product name	Spacial S3D
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	1000 mm
Enclosure nominal width	1000 mm
Enclosure nominal depth	300 mm
Door type	Plain
Mounting plate description	Plain
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	Body 1 Cable gland plate 2 Door with lock 2 Mounting plate 1

Complementary

Variant particularity	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	2 front face	
Door opening side	Reversible 120 °	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Galvanised steel for mounting plate Steel for enclosure	
Surface finish	Epoxy-polyester powder enclosure	
Colour	Grey RAL 7035 enclosure :	
Standards	IEC 62208	
Product certifications	BV CUL DNV GL LR UL	
Product weight	64 kg	

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0810 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available

