NSYS3X101030

SPACIAL S3X stainless 304L, Scotch Brite® finish, H1000xW1000xD300 mm.





Main

Range	Spacial
Product name	Spacial S3X
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	1000 mm
Enclosure nominal width	1000 mm
Enclosure nominal depth	300 mm
Installation accessory type	Wall-mounting
Device composition	1 body 2 door 1 lock (door) 1 reinforcement frame drilled (door)

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail	
Door type	Plain	
Number of doors	Front face : 2 door(s)	
Door opening side	120°, reversible	
Lock type	3 points lock, 3 mm double-bar	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Front	
Removable parts	Door fixing: by hinges	
Material	Lock : zamak Hinge : stainless steel Body and door : stainless steel 304L	
Surface finish	Lock : chromium plated Body and door : Scotch-Brite® brushed	
Thickness	1.5 mm	
Product weight	47 kg	

Environment

standards	IEC 62208	
product certifications	CAN/CSA 22 UL 508 type A	
IP degree of protection	IP55 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
environmental characteristic	Corrosive Specific hygiene	

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0810 - Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	