NSYS3X121030

SPACIAL S3X stainless 304L, Scotch Brite® finish, H1200xW1000xD300 mm.





Main

Range	Spacial
Product name	Spacial S3X
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	1200 mm
Enclosure nominal width	1000 mm
Enclosure nominal depth	300 mm
Installation accessory type	Wall-mounting
Device composition	1 body 2 door 1 lock (door) 1 reinforcement frame drilled (door)

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail	
Door type	Plain	_
Number of doors	Front face : 2 door(s)	
Door opening side	120°, reversible	:
Lock type	3 points lock, 3 mm double-bar	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Front	
Removable parts	Door fixing: by hinges	
Material	Hinge : stainless steel Body and door : stainless steel 304L	
Surface finish	Body and door : Scotch-Brite® brushed	
Thickness	1.5 mm	
Product weight	51.8 kg	

Environment

standards	IEC 62208	
product certifications	CAN/CSA 22 UL 508 type A	
IP degree of protection	IP55 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
environmental characteristic	Corrosive Specific hygiene	

Offer Sustainability

•	
RoHS (date code: YYWW) Complian	t - since 0810 - Schneider Electric declaration of conformity
REACh Reference	e not containing SVHC above the threshold
Product environmental profile Available	
Product end of life instructions Need no	specific recycling operations