NSYS3X3315H

SPACIAL S3X stainless 316L, Scotch Brite® finish, H300xW300xD150 mm.





Main

Range	Spacial
Product name	Spacial S3X
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	300 mm
Enclosure nominal width	300 mm
Enclosure nominal depth	150 mm
Installation accessory type	Wall-mounting
Device composition	1 body 1 door 1 lock (door)

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail	
Door type	Plain	
Number of doors	Front face : 1 door(s)	
Door opening side	120°, reversible	
Lock type	3 mm double-bar lock	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Front	
Removable parts	Door fixing: by hinges	
Material	Lock : zamak Hinge : stainless steel Body and door : stainless steel 316L	
Surface finish	Lock : chromium plated Body and door : Scotch-Brite® brushed	
Thickness	1.5 mm	
Product weight	4.038 kg	

Environment

standards	IEC 62208	
product certifications	CAN/CSA 22 UL 508 type A	
IP degree of protection	IP66 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
environmental characteristic	Corrosive Specific hygiene	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0810 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations