


NSYTRP22BL

Lineryy passthrough terminal block - 2.5mm² 24A
single-level 1x1 push-in - blue



Main

| | |
|------------------------------------|----------------------|
| Range | Lineryy |
| Product name | Lineryy TR |
| Product or component type | Terminal block |
| Device short name | TRP |
| Accessory / separate part category | Connection accessory |
| Terminal block type | Passthrough |
| Terminal block level | 1 |
| Mounting mode | Clip-on |
| Nominal cross section | 2.5 mm ² |
| Length | 48.5 mm |
| Colour | Blue |
| Quantity per set | Set of 50 |

Complementary

| | |
|--------------------------------|--|
| Width | 5.2 mm |
| Height | 36.5 mm |
| Connections - terminals | 1 x push-in : upstream 1 x push-in : downstream |
| Number of terminals | 2 |
| Connection position | Top |
| Number of measurement input | 2 |
| Cable cross section | 0.2...2.5 mm ² , flexible with cable end 0.14...2.5 mm ² , flexible without cable end 0.14...4 mm ² , solid with cable end 0.2...2.5 mm ² , solid without cable end |
| Wire stripping length | 10 mm |
| Tool type | Disconnection : flat screwdriver Connection : without tool |
| [Ue] rated operational voltage | 800 V conforming to EN/IEC 60947-7-1 600 V CSA 600 V cURus |
| [In] rated current | 24 A conforming to EN/IEC 60947-7-1 20 A CSA 20 A cURus |
| Material | Polyamide 6/6 (insulating case) Copper alloy (connector and screw) Copper alloy (commoning link) Chromium-nickel steel (spring) |
| Dielectric loss | 0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4 |
| Dielectric constant | 3.7 at 1 MHz |
| Resistivity | 10000 MΩ.m conforming to IEC 60093 10000 MΩ.m conforming to VDE 0303-T30 |
| Surface resistance | 1000 GΩ conforming to IEC 60093 1000 GΩ conforming to VDE 0303-T30 |
| Creep resistance | 500 CTI (> 400 kV) conforming to IEC 60093 500 CTI (> 400 kV) conforming to VDE 0303-T30 |
| Flame retardance | V0, thickness 0.8 mm conforming to UL 94 |
| Product weight | 7.2 g |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---------------------|--|
| Range compatibility | Prisma - G Prisma - P Pragma Prisma - PH Prisma - Pack Spacial Kaedra TeSys |
|---------------------|--|

| | |
|-----------------------|--------------------|
| Product compatibility | Spacial enclosures |
|-----------------------|--------------------|

Environment

| | |
|------------------------|--|
| product certifications | ATEX CSA CURus GL LR VDE IEC-Ex EAC |
|------------------------|--|

| | |
|---------------------|----------------------------------|
| dielectric strength | 1000 V conforming to IEC 60243-1 |
|---------------------|----------------------------------|

| | |
|---------------------------------------|---|
| ambient air temperature for operation | -40...130 °C conforming to IEC 60216-1 -40...130 °C conforming to VDE 0304-T21 |
|---------------------------------------|---|

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1052 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |