


NSYTRP42TB

Lineryy carrier disc, block - 4mm² 20A single-level
1x1 push-in



Main

Range	Lineryy
Product name	Lineryy TR
Product or component type	Terminal block
Device short name	TRP
Terminal block type	Removable carrier disconnect
Associated connection component	Diode Blade Cylindrical fuse
Terminal block level	1
Mounting mode	Clip-on
Nominal cross section	4 mm ²
Length	56 mm
Colour	Grey
Quantity per set	Set of 50

Complementary

Fuse size	5 x 20 mm 6 x 32 mm
Width	6.2 mm
Height	36.5 mm
Connections - terminals	1 x push-in : upstream 1 x push-in : downstream
Number of terminals	2
Connection position	Top
Number of measurement input	2
Cable cross section	0.2...4 mm ² , flexible without 0.2...6 mm ² , solid
Wire stripping length	10 mm
Tool type	Disconnection : flat screwdriver Connection : without tool
[Ue] rated operational voltage	400 V conforming to EN/IEC 60947-7-1 300 V CSA 300 V cURus
[In] rated current	20 A CSA 20 A conforming to EN/IEC 60947-7-1 20 A cURus
Material	Polyamide 6/6 (insulating case)
Dielectric loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 MΩ.m conforming to IEC 60093 10000 MΩ.m conforming to VDE 0303-T30
Surface resistance	1000 GΩ conforming to IEC 60093 1000 GΩ conforming to VDE 0303-T30
Creep resistance	500 CTI (> 400 kV) conforming to IEC 60093 500 CTI (> 400 kV) conforming to VDE 0303-T30
Flame retardance	V0, thickness 0.8 mm conforming to UL 94
Product weight	9.3 g
Range compatibility	Prisma - G Prisma - P Pragma Prisma - PH

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Prisma - Pack
Spacial
Kaedra
TeSys

Product compatibility	Spacial enclosures
-----------------------	--------------------

Environment

product certifications	CSA CURus GL VDE EAC
dielectric strength	1000 V conforming to IEC 60243-1
ambient air temperature for operation	-40...130 °C conforming to IEC 60216-1 -40...130 °C conforming to VDE 0304-T21

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1052 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold