


# NSYTRR44D

Linery passthrough terminal block - 4mm<sup>2</sup> 28A  
double-level 1x1 spring - grey



## Main

|                                    |                      |
|------------------------------------|----------------------|
| Range                              | Linery               |
| Product name                       | Linery TR            |
| Product or component type          | Terminal block       |
| Device short name                  | TRR                  |
| Accessory / separate part category | Connection accessory |
| Terminal block type                | Passthrough          |
| Terminal block level               | 2                    |
| Mounting mode                      | Clip-on              |
| Nominal cross section              | 4 mm <sup>2</sup>    |
| Length                             | 92.4 mm              |
| Colour                             | Grey                 |
| Quantity per set                   | Set of 50            |

## Complementary

|                                |   |
|--------------------------------|---|
| Width                          | 6.2 mm  |
| Height                         | 55 mm   |
| Connections - terminals        | 1 x spring terminal : upstream<br>1 x spring terminal : downstream  |
| Number of terminals            | 2   |
| Connection position            | Top   |
| Number of measurement input    | 4   |
| Cable cross section            | 0.2...4 mm <sup>2</sup> , flexible with cable end<br>0.08...4 mm <sup>2</sup> , solid without cable end<br>0.08...4 mm <sup>2</sup> , flexible without cable end<br>0.08...6 mm <sup>2</sup> , solid with cable end |
| Wire stripping length          | 10 mm   |
| Tool type                      | Connection : flat screwdriver<br>Disconnection : flat screwdriver   |
| [Ue] rated operational voltage | 500 V conforming to EN/IEC 60947-7-1<br>600 V cURus   |
| [In] rated current             | 30 A cURus<br>28 A conforming to EN/IEC 60947-7-1   |
| Material                       | Polyamide 6/6 (insulating case)<br>Copper alloy (connector and screw)<br>Copper alloy (commoning link)<br>Chromium-nickel steel (spring)  |
| Dielectric loss                | 0.01 at 1 MHz conforming to IEC 60250<br>0.01 at 1 MHz conforming to VDE 0303-T4  |
| Dielectric constant            | 3.7 at 1 MHz  |
| Resistivity                    | 10000 MΩ.m conforming to IEC 60093<br>10000 MΩ.m conforming to VDE 0303-T30   |
| Surface resistance             | 1000 GΩ conforming to IEC 60093<br>1000 GΩ conforming to VDE 0303-T30   |
| Creep resistance               | 500 CTI (> 400 kB) conforming to IEC 60093<br>500 CTI (> 400 kB) conforming to VDE 0303-T30   |
| Flame retardance               | V0, thickness 0.8 mm conforming to UL 94  |
| Product weight                 | 18 g  |
| Range compatibility            | Prisma - G<br>Prisma - P  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Pragma  
Prisma - PH  
Prisma - Pack  
Spacial  
Kaedra  
TeSys

---

|                       |                    |
|-----------------------|--------------------|
| Product compatibility | Spacial enclosures |
|-----------------------|--------------------|

---

## Environment

---

|                                       |   |
|---------------------------------------|---|
| product certifications                | ATEX<br>CSA<br>CURus<br>DNV<br>GL<br>LR<br>VDE<br>IEC-Ex<br>EAC                   |
| dielectric strength                   | 1000 V conforming to IEC 60243-1  |
| ambient air temperature for operation | -40...130 °C conforming to IEC 60216-1<br>-40...130 °C conforming to VDE 0304-T21 |

---

## Offer Sustainability

---

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1052 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations                                 |

---