


## NSYTRV42SF6LD

Fuse disc. terminal, 16mm<sup>2</sup> 10A, 6.3x32mm fuse, LED 12-30V, 1x1 screw, black



### Main

|                           |                    |
|---------------------------|--------------------|
| Range                     | Lineryg            |
| Product name              | Lineryg TR         |
| Product or component type | Terminal block     |
| Device short name         | TRV                |
| Terminal block type       | Fused disconnect   |
| Terminal block level      | 1                  |
| Mounting mode             | Clip-on            |
| Nominal cross section     | 16 mm <sup>2</sup> |
| Length                    | 79 mm              |
| Colour                    | Black              |
| Quantity per set          | Set of 50          |

### Complementary

|                                |                                                                                             |
|--------------------------------|---------------------------------------------------------------------------------------------|
| Fuse size                      | 6.3 x 32 mm                                                                                 |
| Width                          | 10.2 mm                                                                                     |
| Height                         | 60.5 mm                                                                                     |
| Connections - terminals        | 1 x screw terminal : upstream<br>1 x screw terminal : downstream                            |
| Number of terminals            | 2                                                                                           |
| Connection position            | Sideways                                                                                    |
| Number of measurement input    | 0                                                                                           |
| Cable cross section            | 0.5...16 mm <sup>2</sup> , solid<br>0.5...16 mm <sup>2</sup> , flexible without             |
| Tightening torque              | 0.6...0.8 N.m                                                                               |
| Wire stripping length          | 9 mm                                                                                        |
| Tool type                      | Connection : screwdriver<br>Disconnection : screwdriver                                     |
| [Ue] rated operational voltage | 500 V conforming to EN/IEC 60947-7-1<br>600 V CSA<br>600 V cURus                            |
| [In] rated current             | 10 A cURus<br>10 A CSA<br>10 A conforming to EN/IEC 60947-7-1                               |
| Material                       | Polyamide 6/6 (insulating case)                                                             |
| Dielectric loss                | 0.01 at 1 MHz conforming to IEC 60250<br>0.01 at 1 MHz conforming to VDE 0303-T4            |
| Dielectric constant            | 3.7 at 1 MHz                                                                                |
| Resistivity                    | 10000 MΩ.m MΩ.m conforming to IEC 60093<br>10000 MΩ.m MΩ.m conforming to VDE 0303-T30       |
| Surface resistance             | 1000 GΩ GΩ conforming to IEC 60093<br>1000 GΩ GΩ conforming to VDE 0303-T30                 |
| Creep resistance               | 500 CTI (> 400 kV) conforming to IEC 60093<br>500 CTI (> 400 kV) conforming to VDE 0303-T30 |
| Flame retardance               | V0, thickness 0.8 mm conforming to UL 94                                                    |
| Product weight                 | 34.2 g                                                                                      |
| Provided equipment             | Light indicator (12...30 V)                                                                 |
| Range compatibility            | Prisma - G<br>Prisma - P<br>Pragma                                                          |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Prisma - PH  
Prisma - Pack  
Spacial  
Kaedra  
TeSys

|                       |                    |
|-----------------------|--------------------|
| Product compatibility | Spacial enclosures |
|-----------------------|--------------------|

## Environment

|                                       |                                                                                   |
|---------------------------------------|-----------------------------------------------------------------------------------|
| product certifications                | CSA<br>CURus<br>EAC                                                               |
| dielectric strength                   | 1000 V conforming to IEC 60243-1                                                  |
| ambient air temperature for operation | -40...130 °C conforming to IEC 60216-1<br>-40...130 °C conforming to VDE 0304-T21 |

## Offer Sustainability

|                                  |                                                                       |
|----------------------------------|-----------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                 |
| RoHS (date code: YYWW)           | Compliant - since 1052 - Schneider Electric declaration of conformity |
| REACH                            | Reference contains SVHC above the threshold                           |
| Product environmental profile    | Available                                                             |
| Product end of life instructions | Need no specific recycling operations                                 |