



Main

Range of product	Modicon STB distributed I/O solution
Product or component type	BOS internal bus extension kit

Complementary

Kit composition	STBXBA2300 size 2 base STBXBE1300 BOS module STBXTS1120, 2-terminal screw type connector STBXTS2120, 2-terminal spring clamp connector
Mounting location	Beginning of extension segment
Product compatibility	Standard STB modules
[Us] rated supply voltage	24 V
Supply circuit type	DC
Supply voltage limits	19.2...30 V
Input current	400 mA
Output voltage	5.25 V +/- 0.21 % logic bus
Output voltage type	DC
Power supply output current	1.2 A
Electrical connection	2 pins for removable connector power supply Firewire interface
Marking	CE
Overvoltage category	II

Environment

electromagnetic compatibility	Immunity to electromagnetic interference IEC 61131-2
product certifications	CSA FM Class 1 Division 2 UL
pollution degree	2 IEC 60664-1
operating altitude	<= 2000 m
IP degree of protection	IP20 EN 61131-2 class 1
ambient air temperature for storage	-40...85 °C
relative humidity	95 % 60 °C without condensation
vibration resistance	+/-0.35 mm 10...58 Hz 3 gn 58...150 Hz 35 x 7.5 mm symmetrical DIN rail 5 gn 58...150 Hz 35 x 15 mm symmetrical DIN rail
shock resistance	30 gn 11 ms IEC 88 reference 2-27

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold
Product environmental profile	Available

Dimensions

