

# XMLB020P2C11

pressure switch XMLB 20 bar - adjustable scale 2 thresholds - 1 C/O



## Main

|   |  |
|---|--|
| Range of product  | OsiSense XM  |
| Product or component type                               | Electromechanical pressure sensor  |
| Pressure sensor type                                    | Electromechanical pressure sensor  |
| Device short name                                       | XMLB   |
| Pressure sensor size                                    | 20 bar   |
| Controlled fluid  | Viscous product (0...160 °C)   |
| Fluid connection type                                   | G 1 1/4 (female) conforming to ISO 228   |
| Electrical connection                                   | 1 male connector EN 175301-803-A (ex DIN43650) 4 pins  |
| Contacts type and composition                           | 1 C/O  |
| Product specific application                            | -  |
| Pressure switch type of operation                       | Regulation between 2 thresholds  |
| Electrical circuit type                                 | Control circuit  |
| Scale type  | Adjustable differential  |
| Local display   | With   |
| Adjustable range of switching point on rising pressure  | 1.3...20 bar   |
| Adjustable range of switching point on falling pressure | 0.3...18.4 bar   |
| Possible differential maximum at 11 bar high setting    |  |
| Maximum permissible accidental 45 bar pressure          |  |
| Destruction pressure                                    | 90 bar   |
| Pressure actuator                                       | Diaphragm  |
| Materials in contact with fluid                         | FPM, FKM<br>Steel  |
| Enclosure material                                      | Zinc alloy   |
| [In] rated current                                      | 3 A, B300, AC-15 (Ue = 120 V) conforming to EN/IEC 60947-5-1<br>1.5 A, B300, AC-15 (Ue = 240 V) conforming to EN/IEC 60947-5-1<br>0.1 A, R300, DC-13 (Ue = 250 V) conforming to EN/IEC 60947-5-1 |

## Complementary

|   |   |
|---|---|
| Possible differential minimum at low setting  | 1 bar (+/- 0.25 bar)  |
| Possible differential minimum at high setting | 1.6 bar (+/- 0.25 bar)  |
| Maximum permissible pressure - per cycle      | 25 bar  |
| Terminal block type                           | 4 terminals   |
| Operating rate                                | 120 cyc/mn  |
| Repeat accuracy                               | < 2 %   |
| [Ui] rated insulation voltage                 | 500 V conforming to EN/IEC 60947-1<br>300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14 |
| [Uimp] rated impulse withstand voltage        | 6 kV conforming to EN/IEC 60947-1   |
| Auxiliary contacts operation                  | Snap action   |
| Contacts material                             | Silver contacts   |
| Resistance across terminals                   | < 25 mOhm conforming to IEC 255-7 category 3<br>< 25 mOhm conforming to NF C 93-050 method A            |
| Short-circuit protection                      | 10 A cartridge fuse type gG (gl)  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                       |                |
|-----------------------|----------------|
| Mechanical durability | 5000000 cycles |
| Setting               | External       |
| Height                | 130 mm         |
| Depth                 | 76 mm          |
| Width                 | 50 mm          |
| Product weight        | 0.735 kg       |


## Environment

|                                       |  |
|---------------------------------------|--|
| standards                             | CE<br>EN/IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14  |
| product certifications                | BV<br>CCC<br>CSA<br>LROS (Lloyds register of shipping)<br>UL<br>EAC                                  |
| protective treatment                  | TC (standard version)  |
| ambient air temperature for operation | -25...70 °C  |
| ambient air temperature for storage   | -40...70 °C  |
| operating position                    | Any position   |
| vibration resistance                  | 4 gn (f = 30...500 Hz) conforming to IEC 60068-2-6   |
| shock resistance                      | 50 gn conforming to IEC 60068-2-27   |
| electrical shock protection class     | Class I conforming to IEC 1140<br>Class I conforming to IEC 536<br>Class I conforming to NF C 20-030 |
| IP degree of protection               | IP65 conforming to EN/IEC 60529  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Not Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0928 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product end of life instructions | Need no specific recycling operations                                 |


## Dimensions



- (1) 1 fluid entry, tapped G1/4 (BSP female)  
(2) EN 175301-803-A connector


## Wiring Diagram

### Terminal Model




## Wiring Diagram

### Vacuum Switch Connector Pin View




- (1) 11 and 13
- (2) 12
- (3) 14

## Operating Curves



- (y) Rising pressure
- (x) Falling pressure
- 1 : Maximum differential
- 2 : Minimum differential



- (y) Pressure
- (x) Time
- (1) Adjustable value
- PH : High point

PB : Below point