



Main

| | |
|------------------------------|-----------------------|
| Range of product | Harmony |
| Product or component type | Head for pilot light |
| Product specific application | For incandescent bulb |
| Cap/operator or lens colour | White |

Complementary

| | |
|-----------------------|----------------|
| Mechanical durability | 1000000 cycles |
| Product weight | 0.015 kg |

Environment

| | |
|---------------------------------------|---|
| standards | EN/IEC 60947-5-1 CSA C22.2 No 14 |
| protective treatment | TH |
| ambient air temperature for operation | -25...55 °C |
| ambient air temperature for storage | -40...70 °C |
| vibration resistance | 15 gn (10...500 Hz) conforming to IEC 60068-2-6 |
| shock resistance | 100 gn conforming to IEC 60068-2-27 |
| electrical shock protection class | Class II conforming to IEC 61140 |
| overvoltage category | Class II conforming to IEC 61140 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 50102 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.