

56SO532LE-CG

56 Series Socket - 5 Pin - 32A - 500V - Less
Enclosure - Chemical Grey



Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	Chemical grey
Outlet standard	Australian/New Zealand

Complementary

Plug, socket category	Low voltage
Device mounting	Surface
Mounting mode	External mounting
[In] rated current	32 A
[Ue] rated operational voltage	500 V AC @ 50 Hz EN 60309-2
Poles description	3P + N + E
Voltage colour	Black
Duration	7 h
Material	ABS (acrylonitrile butadiene-styrene) for the cover
Contacts material	Brass for the screws
Connections - terminals	Screw terminals 4...16 mm ² cable stiffness rigid or stranded
Tightening torque	0.8 N.m
Socket number	1
Socket-outlet type	S
Outlet standard	Industrial
Product weight	0.44 kg
Depth	74 mm
Width	101 mm
Height	107 mm
Targeted country	Australia

Environment

ambient air temperature for operation	-25...75 °C
standards	AS/NZS 3112

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1650 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.