



garland  
cables

pro series

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.


## Part No: MCP7051S

Description	Stranded 16 AWG PACW, Single Twisted Pairs, V-90HT PVC Insulated, Aluminium Polyester Overall Screen, TACW 22AWG Drain Wire, 5V-90 PVC Sheath.
Applicable Standards	AS/NZS 1125 , AS/NZS 3808 , AS / ACIF S008: 2006, IEC60332-1
Suitable Applications	Instrument and control cable for use in industrial applications including the interconnection of signals between cabinets, consoles, sensors and display panels. Can also be used for carrying low bit rate data signals.
	Not suitable for direct connection to mains voltages.

### Cable Construction Drawing



### Cable Construction Relative Parts



### Cable Description

Conductor	AWG	Standing	Area(mm <sup>2</sup> )	Diameter(mm)	Material
	16	7/0.50	1.5	1.5	PACW
Insulation	Pairs : 10		Material : V-90HT PVC		
	Material :		Black and White wires form a Pair.		
	Colour :		Pair nos. printed on each pair for identification		
	Nominal Thickness (mm) :		0.3		
	Nominal OD (mm) :		2.2		
Screen	Material: Al. Polyester Tape		Coverage: 100%		
Drain Wire	AWG	Standing	Area(mm <sup>2</sup> )	Diameter(mm)	Material
	22	7/0.25	0.34	0.75	TACW

Instrumentation Cable

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99  
www.madisontech.com.au/garland

MCP7051S-150226.docx

made by





garland  
cables

pro series

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Sheath	Material : Colour : Nominal Thickness (mm) : Nominal OD (mm) :	5V-90 PVC Black 0.75 6.1
--------	---	-----------------------------------

### Electrical Properties

Max. Conductor DC Resistance @ 20°C	13.6Ω/km
Min. Impedance @ 1KHz	280ohm
Max. Capacitance Core to Core @ 1KHz	110pF/m
Max. Inductance @ 1KHz	1.1μH/m
Max. Current Rating	13A
Suggest Voltage Rating	110a.c/150d.c

### Mechanical Properties

Operating Temperature Range	-15 to 90°C
Max. Recommended Pulling Tension	166N
Min. Bend Radius (install)	61mm
Approximate Mass	5.8kg/100m
Sheath Printing	GARLAND 1PAIR 1.5mm2 INSTRUMENTATION CABLE MCP7051S - MM/YYYY - "Mmark"

### Supply Information

Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet
500m	Wooden Reel	W39 x H21.8cm	1R	

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99  
www.madisontech.com.au/garland

MCP7051S-150226.docx

made by

