



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Part No: TCW84CL

Description Stranded 13AWG PACW, Figure 8 construction, PVC Insulation.

Applicable Standards AS/NZS 1125, AS/NZS 3808


Suitable Applications For the wiring of electronic and allied equipment, extension speakers,

security system etc.

Cable Construction Drawing

Cable Construction Relative Parts









Cable Description

Conductor	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material
Conductor		2.64	2.11	PACW	
Insulation	Cores: Material: Colour: Nominal Thickness (mm) Nominal OD (mm):			Transparent Pink/Black Stripe : 1.2	

Electrical Properties	
Max. Conductor DC Resistance @ 20°C	7.7 Ω/km
Min. Insulation Resistance @ 20°C	50MΩ.km
Voltage Test: Conductor to core	1.0 kV ac/1min

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the

experts' choice for high quality cables.

Voltage Rating	ELV
Mechanical Properties	
Operating Temperature Range	-15 to 70°C
Max. Recommended Pulling Tension	369N
Min. Bend Radius (install)	45mm
Approximate Mass	8.38kg/100m

Supply Information					
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet	
100m	Plastic Reel	10 x 4.5 x 5.2"	2R		
500m	Wooden Reel	W42 x H21.8cm	1R		

Madison reserves the right to make changes to the products described in this specification without prior notice



All values subject to factory tolerances