

SOFT WALL TUBE

CJS-ST



Features

- Flexible
- Crossed linked polyolefin
- Outstanding physical & chemical properties
- Highly flame retardant
- Excellent electrical properties
- Operating temperature: -45°C to 125°C
- Shrink temperature: 120°C
- RoHS compliant

CATALOGUE NO	SIZE (mm)	AS SUPPLIED	AFTER RECOVERY		STANDARD PACKAGE		LAID FLAT (mm)
		Internal Diameter (mm)	Internal Diameter (mm)	Wall Thickness Nom (mm)	Standard Length (mm)	Spool Length (mtr)	
CJS-ST1	1	1.5 \pm 0.2	0.65	0.28	1200	200	
CJS-ST1.5	1.5	2.0 \pm 0.2	0.85	0.32	1200	200	
CJS-ST2.5	2.5	3.0 \pm 0.2	1.3	0.38	1200	200	5
CJS-ST3.5	3.5	4.0 \pm 0.2	1.8	0.42	1200	200	7
CJS-ST5	5	5.5 \pm 0.2	2.5	0.55	1200	100	9
CJS-ST7	7	7.5 \pm 0.3	3.5	0.55	1200	50	12.5
CJS-ST10	10	10.5 \pm 0.3	5	0.6	1200	50	17
CJS-ST13	13	13.5 \pm 0.3	6.5	0.65	1200	50	22
CJS-ST20	20	21.0 \pm 0.5	10	0.8	1200	50	34
CJS-ST25	25	26.0 \pm 0.5	12.5	0.9	1200	50	42
CJS-ST30	30	31.5 \pm 1.0	15	0.95	1200	50	48
CJS-ST40	40	41.5 \pm 1.0	20	1	1200	25	65
CJS-ST50	50	50	25	1	1200	25	82
CJS-ST70	70	70	36	1.3	1200	15	112
CJS-ST100	100	100	51	1.46	1200	15	152
CJS-ST150	150	150	76	1.56	1200	15	237

** Standard Packaging: Spool or Length (shown above)

**** MORE COLOURS AVAILABLE ****

ASSORTED HEAT SHRINK PACKS



CATALOGUE NO	SIZE (mm)	COLOURS	QTY IN KIT
XLP-BAG-2.5-25	2.5 – 20	R, W, B, BK & GY	110 x 300mm



CATALOGUE NO	SIZE (mm)	COLOURS	QTY IN KIT
XLP-BAG-BLK-2.5-25	2.5 – 20	Black	110 x 300mm



CATALOGUE NO	SIZE (mm)	COLOURS	QTY IN KIT
CJS-XLPC-BOX-150	5 – 25	R, W, B, BK & GY	125 x 150mm



CATALOGUE NO	SIZE (mm)	COLOURS	QTY IN KIT
CJS-XLPB-BOX150	5 – 25	Black	108 x 150mm