



Representative Photo Only  
(actual product may vary based on configuration selections)

ZS70 Series Emergency Pull-wire Switch, Glass-fibre Reinforced Thermoplastic Enclosure, snap action 1NO 1NC, change-over contact with double break, 6A/400V AC switching current, IP67, EN 60947-5-1, -5; EN ISO 13850; EN ISO 13849-1

- Thermoplastic or metal enclosure versions available
- Wide range of output configurations available
- 'Extreme range' switches available - suitable for use in harsh and demanding environments

## SPECIFICATIONS

Component Type Safety	Pull Wire Switch
Details, Safety	B10d (10% Load): 200,000
Output Configuration, Safety	1 NO + 1 NC
E-Stop Button	No
Uimp, Impulse Withstand Voltage	6 kV
Ith, Thermal Current	6 A
Ui, Rated Insulation Voltage	400 V (rms)
Ie, Rated Operational Current, AC-15, 400V	6 A@400V
Fuse Characteristic Type(s)	gL/gG
IP Rating	IP67
Material, Body / Housing	GRP (Glass Reinforced Plastic / Polyester / Thermoplastic) material
Material, Cover	GRP (Glass Reinforced Plastic / Polyester / Thermoplastic) material
Material, Contacts	Silver material
Conduit Entry	M20 x 1.5 entry
Terminal Type	Screw Terminal(s)
Cable Entry Position	Top
Wire / Conductor Size (Max)	2.5 mm <sup>2</sup>
Length, Cable, max	10 m, max
Colour, Cover	Orange colour
Colour, Base	Black base
Height	175 mm
Width	40 mm
Depth	40 mm
Weight	0.236 kg
Mechanical Service Life	100000 cycles
Operating Temperature, Min	-25 °C min
Operating Temperature, Max	70 °C max

Catalogue No: **TQZS701O1SVD**

## SAFETY PULLWIRE SWITCH PLASTIC 1NO1NC 10M PB RESET M20 ENTRY

Safety > Safety Pushbuttons and Operator Devices > Safety Pull Wire Switches > Steute Emergency Stop Pull-wire Switches > Single Sided Actuation > Standard Duty



Standards Compliance	EN 60947-5-1 EN 60947-5-5 ISO 13849-1:2008 / AC:2009 PLc
----------------------	--

Certifications	CCC CSA-US GOST-R
----------------	-------------------------

### REFERENCES

IECEEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-