

Catalogue No: **ZS73SR101S**

BELT-DRIFT SW ALUMINIUM BODY 106X70 SS ROLLER 1NO1NC M20

Field Switching and Sensing > Belt Drift Switches > Belt Drift Switches > Steute Belt Drift Switches > Heavy Duty Belt Drift Switches > ZS 73 Series



Representative Photo Only
(actual product may vary based on configuration selections)

ZS73 Series, Aluminium die-cast enclosure, 70mm x 105mm, Snap action, 1 N/O + 1 NC, 6A/400V AC, IP65

- Extensive range of housing styles available with plastic or metal versions
- Specialised versions with IP69K rating available for high-pressure wash-down applications in the Food and Beverage industry
- High and low temperature tolerance versions available, suitable for applications in extreme environments
- Specialised versions available with 2-stage switching

SPECIFICATIONS

Product Series	ZS 73 SR
Component Type Field Switching & Sensing	Belt Drift Switch
Contact Configuration	1 NO + 1 NC
Contact Type	Double Break type
Material, Contacts	Silver material
Ie, Rated Operational Current, AC-15, 400V	6 A@400V
Cable Cross Section (Max)	2.5 mm ² mm
Cable Entry	2 x [M20 x 1.5]
B10d (ISO 13849:2006)	2000000
Connection / Termination	Screw Terminal(s)
Material, Body / Housing	Enamelled Aluminium, Die-Cast material
Material, Cover	TP (Thermoplastic) material
Uimp, Impulse Withstand Voltage	6 kV
Ui, Rated Insulation Voltage	400 V (rms)
Ithe, Thermal Current, Enclosed	6 A
IP Rating	IP65
Operating Temperature, Min	-25 °C min
Operating Temperature, Max	70 °C max
Depth	98 mm
Width	204 mm
Height	105 mm
Weight	1.3 kg
Standards Compliance	EN 60947-5-1 ISO 13849-1:2008 / AC:2009 PLc
Certifications	CCC EAC CSA-US

Catalogue No: **ZS73SR101S**

BELT-DRIFT SW ALUMINIUM BODY 106X70 SS ROLLER 1NO1NC M20

Field Switching and Sensing > Belt Drift Switches > Belt Drift Switches > Steute Belt Drift Switches > Heavy Duty Belt Drift Switches > ZS 73 Series



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -