## Catalogue No: 700-HPSXZ24

## SAFETY CONTROL RELAY PCB 8A 2P DPDT 24VDC

Timers and Control Relays > General Purpose Relays > Electromechanical Relays > Allen-Bradley Electromechanical Relays > 700-HPS Miniature PCB Pin-Style Safety Relays > 700-HPSX Relays



## Safety control relay PCB 8A 2P DPDT 24VDC

- International approvals that ensure your relay will stand the test of time
- Wide range of relays that provides reliable design, quick replacements and panel space-saving solutions
- Covers the spectrum from PLC switching to High Current loads, ensuring a complete solution



Representative Photo Only

(actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	Bul. 700-HP
Component Type Timers and Control relays	Relay
In, Rated Current	8 A
Contact Breaking Capacity, DC1, 110V	0.65 A
Contact Breaking Capacity, DC1, 220V	0.2 A
Rated Load, AC-1	2000 VA
Coil Voltage, DC, Nom	24 V DC
Material, Contacts	Gold-Plated Silver Nickel material
Insulation Voltage, between Coil & Contacts	250 V
Operating Temperature, Min	-40 °C min
Operating Temperature, Max	70 °C max
Storage Temperature, Min	-50 °C min
Storage Temperature, Max	80 °C max
REFERENCES	
IECEx Certificate -	
Supplier Declaration of Conformity:	
Installation Guide: -	
User Manual: -	

Manufacturer Catalogue & Product Selection:

Manufacturer Datasheet:

\_

\_

