## Catalogue No: **\$1250\$E31250**

## TB2 MCCB 50kA 3P 1250A ELECTRONIC

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 1600 AF > Electronic 1250 / 1600A 1600 AF 50kA





Representative Photo Only (actual product may vary based on configuration selections)

## T2 MCCB 50kA 3P 1250A ELECTRONIC

- Wide range of fault interruption ratings from 25 to 200kA to cater for a wide spectrum of applications
- MCCB sizes available from 16 to 1600A with various common frames and common accessories
- Customer fit accessories available to enable quick and easy configuration
- Basic or Advanced trip units such AC/DC thermal magnetic, AC electronic, metering and communications types are available
- The range complies with AS/NZS IEC 60947-2

SPECIFICATIONS	
Product Series	TemBreak 2 MCCB
Component Type MCCB	AC MCCB
In, Rated Current at 45°C	1250 A @45°C
Un, Nominal Operational Voltage, AC	690 V AC
Ics, Rated Service Short-Circuit Breaking Capacity, AC (IEC 60947)	75 % lcu
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 220/240V AC	85 kA @220/240VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 400/415V AC	50 kA @400/415VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 440V AC	45 kA @440VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 690V AC	20 kA @690VAC
Number of Poles	3
Ui, Rated Insulation Voltage	800 V (rms)
Height	370 mm
Width	210 mm
Standard Installation Method	Front Connection
Reverse Connection Of Supply Possible	Yes
Electrical Service Life at Un, In	4000 cycles
Mechanical Service Life	5000 cycles
Standards Compliance	AS 60947-2 AS/NZS 3947.2 IEC 60947-2
Trip Unit Protection Type	Electronic
Thermal Trip Type	Adjustable type
Ir, Thermal Trip Current, Min	500 A
Ir, Thermal Trip Current, Max	1250 A
Certifications	CE



## Catalogue No: **\$1250\$E31250**TB2 MCCB 50kA 3P 1250A ELECTRONIC



Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 1600 AF > Electronic 1250 / 1600A 1600 AF 50kA

REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

