



Representative Photo Only
(actual product may vary based on configuration selections)

T2 MCCB 630A 3P 70KA ELECTRONIC

- Wide range of fault interruption ratings from 25 to 200kA to cater for a wide spectrum of applications
- MCCB sizes available from 16 to 1600A with various common frames and common accessories
- Customer fit accessories available to enable quick and easy configuration
- Basic or Advanced trip units such AC/DC thermal magnetic, AC electronic, metering and communications types are available
- The range complies with AS/NZS IEC 60947-2

SPECIFICATIONS

Product Series	TemBreak 2 MCCB
Component Type MCCB	AC MCCB
In, Rated Current at 45°C	800 A @45°C
Icw, Short Time Withstand Current, 300ms (rms)	10 kA, 300ms
Un, Nominal Operational Voltage, AC	690 V AC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 220/240V AC	100 kA @220/240VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 400/415V AC	70 kA @400/415VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 440V AC	65 kA @440VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 690V AC	25 kA @690VAC
Frame Size	800 AF size
Number of Poles	3
Ui, Rated Insulation Voltage	800 V (rms)
Height	273 mm
Width	210 mm
Depth	103 mm
Weight	9.1 kg
Standard Installation Method	Front Connection
Reverse Connection Of Supply Possible	Yes
Electrical Service Life at Un, In	4000 cycles
Mechanical Service Life	10000 cycles
Standards Compliance	IEC 60947-2 AS 60947-2 AS/NZS 3947.2
Trip Unit Protection Type	Electronic
Thermal Trip Type	Adjustable type
Ir, Thermal Trip Current, Min	320 A

Catalogue No: **S800RE3800**

TB2 MCCB 70kA 3P 800A ELECTRONIC

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 1000 AF > Electronic 800 / 1000 AF 70kA



Ir, Thermal Trip Current, Max	800 A
Certifications	CE

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-