

# **PRODUCT DATASHEET** HE SL 21 W/830

SMARTLUX T5 HE | Tubular fluorescent lamps 16 mm, high efficiency





## **TECHNICAL DATA**


## Electrical data

| Nominal voltage                     | 220 V   |
|-------------------------------------|---------|
| Nominal wattage                     | 20.60 W |
| Rated lamp efficacy (HF data 25 °C) | 92 lm/W |
| Rated wattage                       | 20.60 W |

## Photometrical data

| Color rendering index Ra | ≥80     |
|--------------------------|---------|
| Rated luminous flux      | 1900 lm |
| Luminous flux at 25 °C   | 1900 lm |
| Luminous flux at 35 °C   | 2100 lm |
| Light color              | 3000    |
| Rated color temperature  | 3000 K  |
| Nominal luminous flux    | 1900 lm |
| Rated LLMF at 2,000 h    | 0.95    |
| Rated LLMF at 4,000 h    | 0.92    |
| Rated LLMF at 6,000 h    | 0.91    |
| Rated LLMF at 8,000 h    | 0.90    |
| Rated LLMF at 12,000 h   | 0.90    |
| Rated LLMF at 16,000 h   | 0.90    |
| Rated LLMF at 20,000 h   | 0.89    |
| Color temperature        | 3000 K  |
| Luminous flux            | 1900 lm |
| Color rendering index Ra | ≥80     |

# Dimensions & weight



| lube diameter | 16 mm    |
|---------------|----------|
| Length        | 849.0 mm |
|               |          |

\_

| Length with base excl. base pins/connection | 849.00 mm |
|---|-----------|
| Diameter                                    | 16.0 mm   |
| Maximum diameter                            | 16.0 mm   |

# Temperatures & operating conditions

| Rated ambient temp.w.max.luminous flux | 35.0 °C |
|--|---------|
|--|---------|

## Lifespan

| Lifespan                               | 20000 h |
|--|---------|
| Rated lamp survival factor at 2,000 h  | 0.99    |
| Rated lamp survival factor at 4,000 h  | 0.99    |
| Rated lamp survival factor at 6,000 h  | 0.99    |
| Rated lamp survival factor at 8,000 h  | 0.99    |
| Rated lamp survival factor at 12,000 h | 0.99    |
| Rated lamp survival factor at 16,000 h | 0.90    |
| Rated lamp survival factor at 20,000 h | 0.50    |
| Operation mode LLMF/LSF                | HF      |
| Rated lamp life time                   | 20000 h |
| Nominal lamp life time                 | 20000 h |

# Additional product data

| Base (standard designation) | G5     |
|-----------------------------|--------|
| Mercury content             | 1.2 mg |
| Show WEEE picto             | Yes    |

## Capabilities


| Suitable for indoor Yes | Suitable for indoor | 163 |
|-------------------------|---------------------|-----|
|-------------------------|---------------------|-----|

#### Certificates & standards

| Energy efficiency class | A+           |
|-------------------------|--------------|
| Energy efficiency class | A+           |
| Energy consumption      | 24 kWh/1000h |

June 12, 2018, 14:05:29 **HE SL 21 W/830** 

## **Light Distribution**



## Spectral power distribution





Circuit diagram

Circuit diagram

#### **LOGISTICAL DATA**

| Product code  | Product description | Packaging unit<br>(Pieces/Unit) | Dimensions (length x width x height) | Volume    | Gross weight |
|---------------|---------------------|---------------------------------|--------------------------------------|-----------|--------------|
| 4008321335463 | HE SL 21 W/830      | Shipping carton box 20          | 891 mm x 104 mm x<br>88 mm           | 8.15 dm³  | 2283.00 g    |
| 4008321339478 | HE SL 21 W/830      | Shipping carton box<br>50       | 899 mm x 204 mm x<br>123 mm          | 22.56 dm³ | 5970.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.