

# PRODUCT DATASHEET

## HE SL 28 W/830

SMARTLUX T5 HE | Tubular fluorescent lamps 16 mm, high efficiency



**TECHNICAL DATA**


Electrical data

Nominal voltage	220 V
Nominal wattage	28.00 W
Rated lamp efficacy (HF data 25 °C)	93 lm/W
Rated wattage	27.90 W

Photometrical data

Color rendering index Ra	≥80
Rated luminous flux	2600 lm
Luminous flux at 25 °C	2600 lm
Luminous flux at 35 °C	2900 lm
Light color	3000
Rated color temperature	3000 K
Nominal luminous flux	2600 lm
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.92
Rated LLMF at 6,000 h	0.91
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Color temperature	3000 K
Luminous flux	2600 lm
Color rendering index Ra	≥80

Dimensions & weight



Tube diameter	16 mm
Length	1149 mm

<b>Length with base excl. base pins/connection</b>	1149.00 mm
<b>Diameter</b>	16.0 mm
<b>Maximum diameter</b>	16.0 mm

#### Temperatures & operating conditions

<b>Rated ambient temp.w.max.luminous flux</b>	35.0 °C
---	---------

#### Lifespan

<b>Lifespan</b>	20000 h
<b>Rated lamp survival factor at 2,000 h</b>	0.99
<b>Rated lamp survival factor at 4,000 h</b>	0.99
<b>Rated lamp survival factor at 6,000 h</b>	0.99
<b>Rated lamp survival factor at 8,000 h</b>	0.99
<b>Rated lamp survival factor at 12,000 h</b>	0.99
<b>Rated lamp survival factor at 16,000 h</b>	0.90
<b>Rated lamp survival factor at 20,000 h</b>	0.50
<b>Operation mode LLMF/LSF</b>	HF
<b>Rated lamp life time</b>	20000 h
<b>Nominal lamp life time</b>	20000 h

#### Additional product data

<b>Base (standard designation)</b>	G5
<b>Mercury content</b>	1.2 mg
<b>Show WEEE picto</b>	Yes


#### Capabilities

<b>Suitable for indoor</b>	Yes
----------------------------	-----


#### Certificates & standards

<b>Energy efficiency class</b>	A+
<b>Energy efficiency class</b>	A+
<b>Energy consumption</b>	31 kWh/1000h

Light Distribution



Spectral power distribution



Circuit diagram

Circuit diagram

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321335562	HE SL 28 W/830	Shipping carton box 20	1191 mm x 104 mm x 88 mm	10.90 dm <sup>3</sup>	2478.00 g
4008321339577	HE SL 28 W/830	Shipping carton box 50	1200 mm x 204 mm x 123 mm	30.11 dm <sup>3</sup>	6340.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.