

Starrett®

www.starrett.com

Recommended Operating Speeds for Bi-Metal Hole Saws

Size	Size	Length	Mild Steel	Tool Steel & Stainless	Cast Iron	Brass	Alum.	Wood
Inch	mm	Feet	RPM	RPM	RPM	RPM	RPM	RPM
9/16	14	0.147	580	300	400	790	900	3000
5/8	16	0.164	550	275	365	730	825	3000
11/16	17	0.180	500	250	330	665	750	3000
3/4	19	0.196	460	230	300	600	690	3000
13/16	21	0.213	425	210	290	580	660	3000
7/8	22	0.229	390	195	260	520	585	3000
1	25	0.262	350	175	235	470	525	2700
1-1/16	27	0.278	325	160	215	435	480	2700
1-1/8	29	0.295	300	150	200	400	450	2700
1-3/16	30	0.311	285	145	190	380	425	2400
1-1/4	32	0.327	275	140	180	360	410	2400
1-5/16	33	0.344	260	135	175	345	390	2400
1-3/8	35	0.360	250	125	165	330	375	2400
1-7/16	37	0.376	240	120	160	315	360	2400
1-1/2	38	0.393	230	115	150	300	345	2400
1-9/16	40	0.409	220	110	145	290	330	2100
1-5/8	41	0.425	210	105	140	280	315	2100
1-1/16	43	0.442	205	100	135	270	305	2100
1-3/4	44	0.458	195	95	130	260	295	2100
1-3/16	46	0.475	190	95	125	250	285	2100
1-7/8	48	0.491	180	90	120	240	270	2100
2	51	0.524	170	85	115	230	255	2000

2-1/16" to 6" on reverse side



Printed in USA

978-249-3551 • www.starrett.com

Recommended Operating Speeds for Bi-Metal Hole Saws

Size	Size	Length	Mild Steel	Tool Steel & Stainless	Cast Iron	Brass	Alum.	Wood
Inch	mm	Feet	RPM	RPM	RPM	RPM	RPM	RPM
2-1/16	52	0.540	165	80	110	220	245	2000
2-1/8	54	0.556	160	80	105	210	240	2000
2-1/4	57	0.589	150	75	100	200	225	2000
2 -5/16	59	0.605	145	75	95	195	225	2000
2-5/8	60	0.622	140	70	90	190	220	2000
2-1/2	64	0.655	135	65	85	180	205	1850
2-9/16	65	0.671	130	65	85	175	200	1850
2-5/8	67	0.687	130	65	85	170	195	1800
2-11/16	68	0.704	130	65	80	170	190	1800
2-3/4	70	0.720	125	60	80	160	185	1800
2-7/8	73	0.753	120	60	75	160	180	1800
3	76	0.785	115	55	70	150	170	1800
3-1/8	79	0.818	110	55	70	140	165	1500
3-1/4	83	0.851	105	50	65	140	155	1500
3-3/8	86	0.884	100	50	65	130	150	1500
3-1/2	89	0.916	95	45	60	130	145	1200
3-5/8	92	0.949	90	45	60	120	140	1200
3-3/4	95	0.982	90	45	60	120	135	1200
3-7/8	98	1.014	90	45	60	120	135	1200
4	102	1.047	85	40	55	110	130	1000
4-1/8	105	1.080	80	40	55	110	120	1000
4-1/4	108	1.113	80	40	55	110	120	900
4-3/8	111	1.145	80	40	50	100	120	900
4-1/2	114	1.178	75	35	50	100	105	900
4-3/4	121	1.244	75	35	50	92	95	900
5	127	1.309	65	30	45	90	90	800
5-1/2	140	1.440	60	25	40	85	85	800
5-3/4	146	1.505	55	25	35	75	75	800
6	152	1.571	55	25	35	75	75	800

(9/16" to 2" on other side)