## **Product Characteristics**

Part Number: WATRK2121

## ELECTRONIC INSTANT IGNITION MICRO TORCH

## **Description:**

Electronic Instant Ignition Micro Torch

- Ideal for situations where a high volume of portable heat source is required for soldering, brazing and heatshrinking
- Butane gas powered with safety lock and instant electronic ignition
- Refillable cordless and portable
- Adjustable flame control
- Suitable for automative, plumbing and working with plastic
- 1300 C heating temperature

| Attribute Name                 | Attribute Value |
|--------------------------------|-----------------|
| Max. temperature               | 1300 °C         |
| Operating time with gas charge | 60 min          |
| Ignition                       | Electronic      |
| Fuel type                      | Butane          |

| Classifications |          |
|-----------------|----------|
| ETIM            | EC001271 |
| UNSPSC          | 23271603 |

Create Date: 09/09/2021

## Disclaimer

For use on datasheets that are created by Rexel

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.