

CABLE CONNECTORS - INSULATED

- Tapered Cable Entry
- Deep Flat / Slotted Screw Head, enabling tight positive connection
- Flame Retardant PVC Insulator
- Brass Connector
- Soft / Pliable Material
- High Quality Jar
- Amp rating is based on the current carrying capacity of the conductor (cable)



Code	Description	Packing	MOQ	Ctn
FCN-16224	2 x 6mm ² Double Screw	50/Jar	1 Jar / 50	18
FCN-16226	2 x 6mm ² Single Screw	100/Jar	1 Jar / 100	18
FCN-16229	2 x 6mm ² Single Screw	500/Jar	1 Jar / 500	4
FCN-16230	2 x 6mm ² Double Screw	300/Jar	1 Jar / 300	4
FCN-16235	2 x 16mm ² Double Screw	10/Box	1 Box / 10	750
FCN-16240	2 x 35mm ² Double Screw	10/Box	1 Box / 10	200
SC1-3x6/50	3 x 6mm ² Single Screw	50/Jar	1 Jar / 50	18

SPECIFICATIONS

	2 x 6mm ² SINGLE	2 x 6mm ² DOUBLE	3 x 6mm ² SINGLE	2 x 16mm ² DOUBLE	2 x 35mm ² DOUBLE
H (mm)	22	22	25.2	38	45
H1 (mm)	20.3	27.2	22.16	44.5	58.5
H2 (mm)	4.8	4.8	4.8	8	11.5
Voltage	450	450	450	450	450

