

RESPIRATORY GEAR

P2 DISPOSABLE RESPIRATOR WITH EXHALATION VALVE

PRODUCT DATA SHEET: PC321



PRODUCT CODE:
PC321



FEATURES AND BENEFITS

- P2: Certified to AS/NZS 1716:2012 Respiratory Protective Devices
- P2 disposable respirator for protection against mechanically and thermally generated particles
- Lightweight cupped design for comfortable extended wear
- Dual latex free elastic straps for ease of donning and doffing
- ProValve exhalation valve for decreased breathing resistance and heat stress
- Nose flange for increased protection and facial fit
- Resealable bag for hygienic storage



WARNINGS AND USE LIMITATIONS

- Facial hair has the potential to compromise the required protective seal of the respirator
- Ensure adequate oxygen levels are present
- Ensure the contamination is known and the respirator is suitable for the application
- Replace when taste, smell or the breathing resistance is high
- Store in a clean, resealable storage device

CARE INSTRUCTIONS

Shelf life of the unopened product is three (3) years from date of manufacture when stored within the temperature range of -20°C to +25°C and less than 80% relative humidity.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.

Ensure disposable mask is correctly fitted prior to each use and conduct annual fit testing in accordance with AS/NZS 1715:2009.

STANDARDS

CERTIFIED TO:
AS/NZS 1716:2012 Respiratory Protective Devices

Certified by Benchmark
Identification number: BMP547903



To be used in conjunction with:
AS/NZS 1715:2009 Selection, Use and Maintenance of Respiratory Protective Equipment

AVAILABLE IN

PRODUCT CODE	QUANTITY	CARTON
PC321-3	3 pieces	30 boxes
PC321	12 pieces	20 boxes

CLASSIFICATION	EFFICIENCY	EXAMPLES OF CONTAINMENTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (Particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (Particles to 0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face & powered air performance at P3 only

PRODUCT DETAILS

Straps: Latex-Free Rubber Band
Filter Media: Polypropylene Melt-blown
Weight: 14g +/- 5g each
Nose Flange: PU Foam

RELATED PRODUCTS

PRODUCT CODE:
PC531



DUST MASKS
P2 + VALVE + CARBON

PRODUCT CODE:
PCFFP2V



DUST MASKS FLAT FOLD
P2 + VALVE

PRODUCT CODE:
PC822



DUST MASKS PROMESH
P2 + VALVE

PRODUCT CODE:
PC823



DUST MASKS PROMESH
P2 + VALVE + CARBON

PRODUCT CODE:
HMTMPM



MAXI MASK 2000
HALF MASK RESPIRATOR
BODY ONLY

AUSTRALIA:
1800 770 723

ADELAIDE:
(613) 9764 9900
SA@PARAMOUNTSAFETY.COM.AU

MELBOURNE:
(613) 9764 9900
VIC@PARAMOUNTSAFETY.COM.AU

SYDNEY:
(612) 9601 3877
NSW@PARAMOUNTSAFETY.COM.AU

NEW ZEALAND:
0800 770 723
NZ@PARAMOUNTSAFETY.CO.NZ

BRISBANE:
(617) 3806 2699
QLD@PARAMOUNTSAFETY.COM.AU

PERTH:
(618) 9301 7888
WA@PARAMOUNTSAFETY.COM.AU

PROCHOICESAFETYGEAR.COM

