

TRACEABLE FIBREGLASS ROD AND FRAME - 4.5MM X 30M

The MSS range of fibreglass rods have a copper trace wire running through the core making them suitable for underground cable and conduit locating with the use of an appropriate locator.

The rod is supplied complete with brass male ends and hauling eye and is fitted to a sturdy zinc plated steel frame with a brake.

FEATURES & BENEFITS

- Suitable for underground cables and conduit locating with the use of a suitable locator
- Supplied complete with brass ends and hauling eye
- Copper trace wire running through the core
- Fitted to a sturdy zinc plated steel frame with brake






ORDERING INFORMATION

PART NO.	DESCRIPTION	SIZE x LENGTH
MSS-4.5-30	Traceable Fibreglass Rod and Frame	4.5mm x 30m
MSS-4.5-60	Traceable Fibreglass Rod and Frame	4.5mm x 60m
MSS-4.5-80	Traceable Fibreglass Rod and Frame	4.5mm x 80m
MSS-4.5-100	Traceable Fibreglass Rod and Frame	4.5mm x 100m

ALSO AVAILABLE

PART NO.	DESCRIPTION	SIZE x LENGTH
MSS-RFL-4.5-30	Refill Coil	4.5mm x 30m
MSS-RFL-4.5-60	Refill Coil	4.5mm x 60m
MSS-RFL-4.5-80	Refill Coil	4.5mm x 80m
MSS-RFL-4.5-100	Refill Coil	4.5mm x 100m
MSS-JK4.5-3.0	Repair/Jointing Kit	-
MSS-4.5FLEX	Flexible spring leader	-



				
ø 4,5 mm	ø 40-60 mm	310 mm	1100 kg	170 kg

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.