



IP56 Braided Extension Leads

FEATURES
Available with either 10 Amp or 15 Amp
80 % screen is EMC Compliant
Tinned Copper Screen For Mechanical
Tinned Copper Screen Earthed For Fault Protection
Excellent Flexibility

PACKAGING
All Leads already Labelled with Length & Part No

Product Code	Length	Cable Size mm2	Cable Amps	Plug And Socket Amps
BXLIP5610M10A	10 MTR	1.5	15	10
BXLIP5615M10A	15 MTR	1.5	15	10
BXLIP5620M10A	20 MTR	1.5	15	10
BXLIP5630M10A	30 MTR	2.5	25	10
BXLIP5610M15A	10 MTR	1.5	15	15
BXLIP5615M15A	15 MTR	1.5	15	15
BXLIP5620M15A	20 MTR	1.5	15	15
BXLIP5630M15A	30 MTR	2.5	25	15

Please Note**

Amperage ratings specified are in accordance with AS/NZS 3008.1.1.2009 Table 14 (Flexible "Spaced").

Please Note

Please consult with your Electrician / Engineer to ensure this cable is suitable for the intended application and installation.

Elcon Cables takes every precaution to ensure the information in this publication is correct but accepts no liability of any kind and reserves the right to change any detail in this catalogue without notification.

<p>NSW TEL 02 9602 4888 FAX 02 9602 4099 EMAIL salesnsw@elconcables.com.au</p>	<p>QLD TEL 07 3805 6455 FAX 07 3805 6433 EMAIL salesqld@elconcables.com.au</p>	<p>VIC TEL 03 9558 1044 FAX 03 9551 5844 EMAIL salesvic@elconcables.com.au</p>
<p>WA TEL 08 9358 1809 FAX 08 9358 2182 EMAIL saleswa@elconcables.com.au</p>	<p>www.elconcables.com.au</p>	
		<p>SA TEL 08 8326 4833 FAX 08 8326 4855 EMAIL salessa@elconcables.com.au</p>