

## Product data sheet

### Characteristics

# 757364CN

## Fuse, Fusarc CF, indoor, 12kV, 125A, 442mm



### Main

Range of product	Fusarc CF
Quality labels	ISO 14001 ISO 9001
Standards	IEC 60282-1 IEC 60787 DIN 43625 VDE 0670-402
Product or component type	Fuse
Protection technology	Current limiter Thermal limiter

### Complementary

[In] rated current	125 A
Rated voltage (Ur)	12 kV
[Ue] rated operational voltage	6...12 kV
Maximum discharge current	40 kA
Braking current	650 A
Average resistance	5.3 mOhm at 20 °C +/- 10 %
Power dissipation in W	143 W
Type of installation	Indoor
Material	Glass fiber
Product destination	Motor Power transformer Capacitor Voltage transformer
Condition of use	Cubicle In open air Fuse chamber
Length	442 mm
Net weight	5 kg
Diameter	86 mm

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.5 cm
Package 1 Width	9.5 cm
Package 1 Length	51.0 cm
Package 1 Weight	4.98 kg
Unit Type of Package 2	P12
Number of Units in Package 2	48
Package 2 Height	50.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	244.32 kg