Technical data sheet

Exit LED Signature exit LED Quickfit[®] vandal resistant

s·Range



Range

Signature range

Product group

Exit LED

Features

- 3 year warranty
- LED technology 100,000 hours lamp life
- IK09 mechanical impact resistance
- Vermin resistance
- Advanced pulsetime dual rate battery charger with high temperature NiCad batteries
- Unique internal steel slide connect bracket for quick installation and easy maintenance
- Strong steel body and end cap
- Anti-tamper cover screws
- Universal wall/ceiling mounting
- Includes all pictograph diffuser options for single or double sided installation



140mm



Standard products

Catalogue no.	Description
VPQLED	LED Quickfit vandal resistant pictograph exit

Spare parts

Catalogue no.	Description
03-01218	Battery 4 cell NiCad 4.8V 1.8Ah
PQFLED-FR	LED Quickfit exit frame only

Dimensions

Length	Width	Height
410mm	140mm	265mm

Weight

Model	Weight
Standard	7.8kg

Construction

Part	Construction	
	Steel body and end cap with anti-tamper cover screws White powder coated finish	
Diffuser	Extra tough UV stabilised polycarbonate	

Light source

Model	Light source
Standard	Multiple LED 1.6W

Power consumption

Model	Power consumption
Standard	3.6W

Photometrics

Model	Class	Classification
Standard	Со	E1.25
	C90	E1.25

Note: Preliminary results

Note: Designed to comply with AS2293 and meet relevant Australian EMC standards



