



Main

Product or component type	Communication card
Range compatibility	Altivar 61 Altivar 71
Communication port protocol	Profinet MRP (Media Redundancy Protocol)
Connector type	2 RJ45 connectors
Transmission rate	100 Mbits
Physical interface	RJ45 for Profinet
Web services	Data editor Drive monitor Drive parameters Drive recorder Ethernet/IP setup Ethernet statistics FDR Agent Security IPar client settings Save/restore drive configuration Multi-language services

Complementary

Exchange mode	Full duplex
Communication data link	LLC : IEEE 802.2 MAC : IEEE 802.3
Communication network type	Ethernet CiA 402 profile conforming to IEC 61800-7-201 Ethernet PROFIdrive profile
Communication transport type	TCP CiA 402 profile conforming to IEC 61800-7-201 UDP PROFIdrive profile RT (real-time)
Web server	Embedded
Communication service	FTP IPar-server
Display type	1 LED for Link (Link Status) 1 LED for MS (Module Status) 1 LED for NS (Network Status) 1 LED for TX/RX (Transmit/Receive port 1) 1 LED for TX/RX (Transmit/Receive port 2)
Product weight	0.287 kg

Environment

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1312 - Schneider Electric declaration of conformity