




Flexible cord and Cable – Multi Core Ordinary Duty

250/440V PVC V90 copper conductor Flexible Cable.



Application: 2 core ordinary duty cords can be used in dry situations for double insulated applications and luminaries such like hand held lamps, sewing machines and office machines, where the cord may be subject to some mechanical stress but not rough usage.

3 core ordinary duty cords can be used for extension leads and for domestic appliances.

4 and 5 ordinary duty cords are suitable for industrial and office equipment requiring three phase supply and earth connection

Conductor: Plain annealed copper wire

Insulation: PVC 90°C (AS/NZS 3808)

Sheath: PVC 90°C

Voltage: 250/440V

Standards: AS/NZS 3191

Pack Length: 100m, 500

Typical Features:

Electra Cables Part No.	Nom. area mm ²	Stranding No/mm	Nom. O.D. mm	Insulation Thickness mm	Sheath Thickness mm	Amp Rating	Max. Cond.DC. Resistance @ 20°C Ω/km
F2075	0.75	24/0.20×2	6.4	0.6	0.8	7.5	26.0
F2010	1.0	32/0.20×2	6.7	0.6	0.8	10	19.5
F2015	1.5	30/0.25×2	7.7	0.7	0.8	15	13.3
F3075	0.75	24/0.20×3	6.8	0.6	0.8	7.5	26
F3010	1.0	32/0.20×3	7.1	0.6	0.8	10	19.5
F3015	1.5	30/0.25×3	8.3	0.7	0.9	15	13.3
F3025	2.5	50/0.25×3	10.2	0.8	1.1	20	7.98
F3040	4.0	56/0.30×3	11.4	0.8	1.1	25	4.95
F3060	6.0	84/0.30×3	13.5	0.8	1.3	40	3.30
F4075	0.75	24/0.20×4	7.3	0.6	0.8	7.5	26
F4010	1.0	32/0.20×4	7.9	0.6	0.9	10	19.5
F4015	1.5	30/0.25×4	9.3	0.7	1.0	15	13.3
F4025	2.5	50/0.25×4	11.1	0.8	1.1	20	7.98
F4040	4.0	56/0.30×4	12.5	0.8	1.1	25	4.95
F4060	6.0	84/0.30×4	15.0	0.8	1.4	40	3.30