

Data Sheet

10A & 15A Power Centre with RCBO Protection

CAT NO. REPC410, REPC415 and REPC410USB



Product specifications	
Cat No	REPC410, REPC415, REPC410USB
Supply voltage	230-240V a.c. 50Hz
Max load	2400W (10A) 3600W (15A)
Rated residual current	30mA
Typical trip time	30ms
Lead	1.0mm flexible heavy duty - 1.8m (10A) 1.5mm flexible heavy duty - 1.8m (15A)
Rated	IP33

10A & 15A Power Centre with RCBO Protection

CAT NO. **REPC410**, **REPC415** and **REPC410USB**



- Ideal for construction sites and workshops.
Site suitable AS/NZS3012
- Built in RCBO protection (combines the features of a RCD and MCB)
- RCD (Residual Current Device) provides a fast power cut off to reduce the risk of electrocution
- MCB (Miniature Circuit Breaker) protects the power centre from damage under overload conditions
- Double pole shuttered outlets for extra safety
- Parking clip for convenience
- Orange heavy-duty high visibility lead for extra safety
- 1.8m lead
- REPC410USB: 2 x 2.4A charging USB ports
- Rated IP33 weatherproof
- Compatible with portable appliance testers
- 2-year warranty

Cat No REPC410		
Single product		
Barcode	Dimensions	Weight
9321001370222	150(L) x 134(W) x 189(H)mm	1260g

Outer box (Qty 9)		
Barcode	Dimensions	Weight
9321001370239	470(L) x 420(W) x 220(H)mm	12.9kg (G.W.)

Cat No REPC415		
Single product		
Barcode	Dimensions	Weight
9321001370246	150(L) x 134(W) x 189(H)mm	1300g

Outer box (Qty 9)		
Barcode	Dimensions	Weight
9321001370253	470(L) x 420(W) x 220(H)mm	12.9kg (G.W.)

Cat No REPC410USB		
Single product		
Barcode	Dimensions	Weight
9321001431114	150(L) x 134(W) x 189(H)mm	1260g

Outer box (Qty 9)		
Barcode	Dimensions	Weight
9321001431121	470(L) x 420(W) x 220(H)mm	12.9kg (G.W.)

HPM Legrand - AUS
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

HPM Legrand - NZ
0800 476 009
www.legrand.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or
HPM Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.