

AUTOMATION ENCLOSURE PART #BB03



- 81 poles over 3 rows of 27 pole din rail
- 300mm wide cable tray for cable dressing and securing
- Lift off hinges which can be field reversed for opposite door swing
- 6 x individual neutral and 6 x individual earth bars
- 24 pole main earth and neutral bars
- 600mm (H) x 800mm (W) x 220mm (D)
- Removable hinged escutcheon
- **AUSTRALIAN MADE**



SPECS

CONSTRUCTION		SUPPLIED WITH	
ENCLOSURE MATERIAL	1.6mm sheet metal	24 pole main earth and 24 pole main neutral bars	
ESCUTCHEON	1.6mm steel with fixing screw	6 x 12 pole earth and 6 x 12 pole neutral bars	
DOOR LOCK	1 x flush Key Lock CL001	6 x 50mm snap bushes	
CABLE ENTRY	Top/bottom removable gland plates	Cable ties	
MOUNTING	Surface or recess	Heat shrink red, white, blue, black and earth	
SIZE	600mm(H) x 800mm(W) x 220mm(D)	Circuit identification stickers	
		Circuit schedule card	
		Pole filler strips	
TECHNICAL		ORDERING INFORMATION**	
DEGREE OF PROTECTION	IP42 – to AS.1939.1	BB03W	White powder coat
FORM OF SEGREGATION	Form 1 – to AS.3439.1	BB03BK	Black powder coat
BOARD LOCATION	Indoor		
POLES	81 poles over 3 rows of 27 pole din rail		

****Custom colours available, made to order**

AUTOMATION ENCLOSURE PART #BB06



- 162 poles over 6 rows of 27 pole din rail
- 300mm wide cable tray for cable dressing and securing
- Lift off hinges which can be field reversed for opposite door swing
- 12 x individual neutral and 12 x individual earth bars
- 42 pole main earth and neutral bars
- 1200mm (H) x 800mm (W) x 220mm (D)
- Removable hinged escutcheon
- **AUSTRALIAN MADE**



SPECS

CONSTRUCTION		SUPPLIED WITH	
ENCLOSURE MATERIAL	1.6mm sheet metal	42 pole main earth and 42 pole main neutral bars	
ESCUTCHEON	1.6mm steel with fixing screw	12 x 12 pole earth and 12 x 12 pole neutral bars	
DOOR LOCK	1 x Flush Key Lock CL001	7 x 50mm snap bushes	
CABLE ENTRY	Top/bottom removable gland plates	Cable ties	
MOUNTING	Surface or recess	Heat shrink red, white, blue, black and earth	
SIZE	1200mm(H) x 800mm(W) x 220mm(D)	Circuit identification stickers	
		Circuit schedule card	
		Pole filler strips	
TECHNICAL		ORDERING INFORMATION**	
DEGREE OF PROTECTION	IP42 – to AS.1939.1	BB06W	White powder coat
FORM OF SEGREGATION	Form 1 – to AS.3439.1	BB06BK	Black powder coat
BOARD LOCATION	Indoor		
POLES	162 poles over 6 rows of 27 pole din rail		

****Custom colours available, made to order**

AUTOMATION ENCLOSURE PART #BB07



- 189 poles over 7 rows of 27 pole din rail
- 300mm wide cable tray for cable dressing and securing
- Lift off hinges which can be field reversed for opposite door swing
- 14 x individual neutral and 14 x individual earth bars
- 42 pole main earth and neutral bars
- 1400mm (H) x 800mm (W) x 220mm (D)
- Removable hinged escutcheon
- **AUSTRALIAN MADE**



SPECS

CONSTRUCTION		SUPPLIED WITH	
ENCLOSURE MATERIAL	1.6mm sheet metal	42 pole main earth and 42 pole main neutral bars	
ESCUTCHEON	1.6mm steel with fixing screw	14 x 12 pole earth and 14 x 12 pole neutral bars	
DOOR LOCK	2 x Flush Key Lock CL001	7 x 50mm snap bushes	
CABLE ENTRY	Top/bottom removable gland plates	Cable ties	
MOUNTING	Surface or recess	Heat shrink red, white, blue, black and earth	
SIZE	1400mm(H) x 800mm(W) x 220mm(D)	Circuit identification stickers	
		Circuit schedule card	
		Pole filler strips	
TECHNICAL		ORDERING INFORMATION**	
DEGREE OF PROTECTION	IP42 – to AS.1939.1	BB07W	White powder coat
FORM OF SEGREGATION	Form 1 – to AS.3439.1	BB07BK	Black powder coat
BOARD LOCATION	Indoor		
POLES	189 poles over 7 rows of 27 pole din rail		

****Custom colours available, made to order**

AUTOMATION ENCLOSURE PART #BB09



- 243 poles over 9 rows of 27 pole din rail
- 300mm wide cable tray for cable dressing and securing
- Lift off hinges which can be field reversed for opposite door swing
- 18 x individual neutral and 18 x individual earth bars
- 42 pole main earth and neutral bars
- 1800mm (H) x 800mm (W) x 220mm (D)
- Removable hinged escutcheon
- **AUSTRALIAN MADE**



SPECS

CONSTRUCTION	
ENCLOSURE MATERIAL	1.6mm sheet metal
ESCUTCHEON	1.6mm steel with fixing screw
DOOR LOCK	2 x Flush Key Lock CL001
CABLE ENTRY	Top/bottom removable gland plates
MOUNTING	Surface or recess
SIZE	1800mm(H) x 800mm(W) x 220mm(D)

TECHNICAL	
DEGREE OF PROTECTION	IP42 – to AS.1939.1
FORM OF SEGREGATION	Form 1 –to AS.3439.1
BOARD LOCATION	Indoor
POLES	243 poles over 9 rows of 27 pole din rail

SUPPLIED WITH	
42 pole main earth and 42 pole main neutral bars	
18 x 12 pole earth and 18 x 12 pole neutral bars	
10 x 50mm snap bushes	
Cable ties	
Heat shrink red, white, blue, black and earth	
Circuit identification stickers	
Circuit schedule card	
Pole filler strips	

ORDERING INFORMATION	
BB09W	White powder coat
BB09BK	Black powder coat

***Custom colours available, made to order*